



Material Safety Data Sheet

Sikaflex®-292i

1. Product and company identification

Product name : Sikaflex®-292i
Supplier : Sika Corporation, Industry
30800 Stephenson Highway
Madison Heights, MI 48071
www.sikaindustry.com
Telephone no. : (888) 832 - 7452
Fax no. : (248) 577 - 0810
In case of emergency : CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887
Manufacturer : Sika Corporation, Operations
201 Polito Avenue
Lyndhurst, NJ 07071
www.sikacorp.com
Telephone no. : (201) 933 - 8800
Validation date : **9. September 2011.**
Print date : 9. September 2011.
Product type : Liquid.

2. Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich reaction product of polyol with toluene diisocyanate	68515-49-1	10 - 30
Silane, dichlorodimethyl-, reaction products with silica	Mixture	10 - 30
	68611-44-9	1 - 5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

3. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential acute health effects

Inhalation : Slightly irritating to the respiratory system.
Ingestion : Harmful if swallowed.
Skin : Irritating to skin.
Eyes : Irritating to eyes.

See toxicological information (Section 11)

4. First aid measures

Eye contact : Check for and remove any contact lenses. Get medical attention. Immediately flush eyes with plenty of water for at least 15 minutes.
Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse.
Inhalation : Get medical attention immediately. Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Maintain an open airway. In the event of any complaints or symptoms, avoid further exposure.

4 . First aid measures

- Ingestion** : Get medical attention immediately. Wash out mouth with water. Move exposed person to fresh air. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5 . Fire-fighting measures

- Flammability of the product** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
halogenated compounds
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain

7 . Handling and storage

product residue and can be hazardous. Do not reuse container.

- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8 . Exposure controls/personal protection

Consult local authorities for acceptable exposure limits.

- Engineering measures** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

9 . Physical and chemical properties

- Flash point** : Closed cup: 100°C (212°F)
- Color** : Various
- Odor** : Characteristic.
- Density** : ~1.3 g/cm³ [20°C (68°F)]
- VOC** : 22.8 g/l
- Solubility** : Insoluble in the following materials: cold water.

10 . Stability and reactivity

- Stability** : The product is stable.
- Conditions to avoid** : No specific data.
- Materials to avoid** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Hazardous polymerization** : Under normal conditions of storage and use, hazardous polymerization will not occur.

11 . Toxicological information

Potential chronic health effects

Chronic effects : Contains material that may cause target organ damage, based on animal data.

Acute toxicity

Conclusion/Summary : Not available.

12 . Ecological information

Environmental effects : No known significant effects or critical hazards.

13 . Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14 . Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Additional information
DOT Classification	Not regulated.		-	-	-
TDG Classification	Not regulated.		-	-	-
ADR/RID Class	Not regulated.		-	-	-
IMDG Class	Not regulated.		-	-	-
IATA-DGR Class	Not regulated.		-	-	-

PG* : Packing group

15 . Regulatory information

U.S. Federal regulations :

United States inventory (TSCA 8b): All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found.

SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: Limestone; Ethylene, chloro-, polymer; titanium dioxide

SARA 311/312 MSDS distribution - chemical inventory - hazard identification:

Limestone: Immediate (acute) health hazard; Ethylene, chloro-, polymer: Delayed (chronic) health hazard; titanium dioxide: Immediate (acute) health hazard

Clean Water Act (CWA) 307: ethylbenzene

Clean Water Act (CWA) 311: n-butyl acetate; ethylbenzene; xylene

Clean Air Act (CAA) 112 accidental release prevention: No products were found.

State regulations :

Massachusetts Substances:

The following components are listed:
CALCIUM CARBONATE; TITANIUM DIOXIDE

New Jersey Hazardous Substances:

The following components are listed:
CALCIUM CARBONATE;
LIMESTONE; TOLUENE
DIISOCYANATE (mixed isomers);
BENZENE, 1,3-
DIISOCYANATOMETHYL-;
TITANIUM DIOXIDE; TITANIUM OXIDE (TiO₂); PVC; ETHENE, CHLORO-, HOMOPOLYMER

New York Acutely Hazardous Substances:

The following components are listed:
Toluene diisocyanite

Pennsylvania RTK Hazardous Substances:

The following components are listed:
LIMESTONE; BENZENE, 2,4-
DIISOCYANATOMETHYL-;
TITANIUM OXIDE (TiO₂)

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

<u>Ingredient name</u>	<u>Cancer</u>	<u>Reproductive</u>	<u>No significant risk level</u>	<u>Maximum acceptable dosage level</u>
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	No.	Yes.	No.	No.

United States inventory (TSCA 8b) : All components are listed or exempted.

16 . Other information

Hazardous Material Information System (U.S.A.) :

Health	*	2
Flammability		1
Physical hazards		0
Personal Protection Equipment		C

16 . Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Date of printing : 09.09.2011.

Date of issue : 09.09.2011.

Date of previous issue : 09.09.2011.

Version : 1.04

☑ Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800.