

# Material Safety Data Sheet

MSDS Number: C6034F

Issue Date: 11/13/1985

Product Name: S-300, GPA, GPM, GPS, UVT

Revised Date: 12/15/2004

Aristech Acrylics LLC  
7350 Empire Drive  
Florence, KY 41042

Emergency:  
(859) 283-1501 (8 a.m. – 5 p.m. Mon-Fri)  
(800) 424-9300 (Off-Hour Emergencies)

## Section 1 – Product Identification

Product Name: S-300, GPA, GPM, GPS, UVT  
Synonyms: Acrylic Sheet  
Chemical Name: Polymethylmethacrylate

## Section 2 – Composition/Information on Ingredients

| Ingredient Name                               | CAS No.    | % WT | Exposure Limits   |
|---|------------|------|---|
| *S-300, GPA, GPM, GPS, UVT                    | Mixture    | 100  | This product can generate Particulates Not Otherwise Classifiable (PNOC). The OSHA PEL-TWA for PNOC is 15 mg/m <sup>3</sup> (total dust) and 5 mg/m <sup>3</sup> (respirable fraction). The ACGIH TLV-TWA for PNOC is 10 mg/m <sup>3</sup> (inhalable) and 3 mg/m <sup>3</sup> (respirable fraction). |
| Colorants                                     | N/A        | ~2   | Y (Hazardous)**<br>N/A – OSHA PEL TWA<br>N/A – ACGIH TLV TWA  |
| Butyl acrylate, methyl methacrylate copolymer | 25852-37-3 | ~98  | N (Hazardous)<br>N/A – OSHA PEL TWA<br>N/A – ACGIH TLV TWA  |
| Methyl methacrylate                           | 80-62-6    | 1-2  | Y (Hazardous)**<br>100 ppm (OSHA PEL TWA)<br>50 ppm (ACGIH TLV TWA)<br>100 ppm (ACGIH STEL CEILING)   |

\* Mixture. Chemicals that follow this listed chemical are part of the listed mixture.

\*\* All ingredients in quantities >1.0% (>0.1% for carcinogens) that are potentially hazardous per OSHA definitions

Some States enforce the PELs that OSHA promulgated in 1989, which were subsequently vacated by the U.S. Supreme Court. Check with your state OSHA agency to determine which PEL is enforced in your jurisdiction.

# Material Safety Data Sheet

MSDS Number: C6034F

Issue Date: 11/13/1985

Product Name: S-300, GPA, GPM, GPS, UVT

Revised Date: 12/15/2004

## Section 3 – Hazard Identification

### Emergency Overview:

CAUTION! Inhalation of dusts or vapors may cause upper respiratory tract irritation with coughing and a burning sensation in the throat. Repeated skin exposures to dusts may cause allergic skin reactions.

### Potential Health Effects:

**Eyes:** Transient/mechanical irritation from contact with dusts. Possible irritation from operations and processing vapors or dusts.

**Skin:** Possible transient/mechanical irritation.

**Ingestion:** Product in marketed form is inert.

**Inhalation:** Sawing, sanding, grinding, or burning may cause upper respiratory tract irritation

**Relevant Routes of Exposure:** Inhalation, eye and skin.

### Signs and Symptoms of Acute Overexposure:

Product sold in its marketed form is not expected to present a serious health hazard; however, operations such as sawing, sanding, grinding or burning may generate dust, smoke or vapors which may be irritating. Inhalation of such dusts, smoke and vapors may cause upper respiratory tract irritation. Symptoms may include burning sensation, coughing, sneezing, and sore throat. Skin contact with dust may produce transitory mechanical irritation. Symptoms may include redness and itching. High concentrations of dusts may cause irritation to the eyes causing burning, redness, and tearing. This product is not expected to be toxic if ingested.

### Signs and Symptoms of Chronic Overexposure:

Prolonged or repeated over exposures to high concentrations may cause coughing, dizziness, confusion, headache and drowsiness. Prolonged or repeated skin contact may lead to allergic skin reactions.

### Medical Conditions Generally Aggravated By Exposure:

Individuals with chronic respiratory disorders may be adversely affected by any fume or airborne particulate matter exposure. Persons with preexisting skin disorders may be more susceptible to the effects of this material.

### Carcinogenicity:

NTP: N\*

IARC: N\*

OSHA: N/A

ACGIH: N/A

OTHER: N/A

### Additional Information If Applicable

\*Cadmium: Cadmium and Cadmium Compounds are listed as undifferentiated in IARC and the Annual NTP Report as carcinogenic to animals, but with only limited and conflicting evidence of carcinogenicity to humans. These listings are

# Material Safety Data Sheet

MSDS Number: C6034F

Issue Date: 11/13/1985

Product Name: S-300, GPA, GPM, GPS, UVT

Revised Date: 12/15/2004

based on test results for Cadmium Compounds other than the pigmentary forms, which are not contained in this product (i.e., oxides and metals). Limited studies have suggested that human exposure to cadmium (primarily as the oxide) is associated with an increased risk of cancer. Various cadmium salts have been shown to cause local sarcomas, testicular atrophy (i.e., decreased size) and testicular tumors in laboratory animals following intravenous and subcutaneous injections.

## Section 4 – First Aid Measures

### Eyes:

Flush immediately with plenty of cool water for at least 15 minutes. Call a physician immediately.

### Skin:

Wash affected area with soap and plenty of water. If irritation develops, call a physician.

### Ingestion:

Product in its marketed form is inert. If large amounts are swallowed, call physician, immediately.

### Inhalation:

For overexposure to heated resins, remove from exposure. If breathing is difficult, or has stopped, administer artificial respiration (mouth-to-mouth) or oxygen as indicated. Call a physician, immediately.

**Notes to Physicians:** None known.

## Section 5 – Fire Fighting

**Flammable Limits in Air (% by Volume):** N/A

**Flash Point:** N/A

### Extinguishing Media:

Use water or dry chemicals to extinguish fire.

### Fire Fighting Instructions:

Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing when fighting fires. Use cold water spray to cool fire-exposed containers.

### Unusual Fire and Explosion Hazards:

Burning material may give off toxic products of combustion (CO, CO<sub>2</sub>) when involved in a hot fire.

### Known or Anticipated Hazardous Products of Combustion:

Combustion products may include carbon dioxide, carbon monoxide, methyl methacrylate monomer (MMA) and acrid smoke and fumes.

## Section 6 – Accidental Release Measures

**Accidental Release Measures and Methods for Cleanup:**

# Material Safety Data Sheet

MSDS Number: C6034F

Issue Date: 11/13/1985

Product Name: S-300, GPA, GPM, GPS, UVT

Revised Date: 12/15/2004

If released or spilled, product may be cleaned up and disposed in the trash. Allow hot or heated material to solidify and cool before disposal.

## Section 7 – Handling and Storage

### Handling:

Avoid breathing of vapors, fumes and smoke which may be released during thermal processing. Since finished product has sharp edges, protective gloves should be worn when handling.

### Storage:

Store in cool dry area.

## Section 8 – Exposure Controls/Personal Protection

### Ventilation Requirements:

Local exhaust ventilation should be used to control the emissions of air contaminants. General dilution ventilation may assist with the reduction of air contaminant concentrations.

### Personal Protective Equipment:

#### Eye/Face:

Employees should be required to wear chemical safety goggles to prevent eye contact. A face shield should be used when appropriate to prevent contact with hot material.

#### Skin:

When necessary, garments for protection against heated materials should be used to prevent skin contact with hot acrylate polymer. Since finished material has sharp edges, wear protective gloves when handling. Polyvinyl alcohol and Teflon® protective garments have been recommended for protection against methyl methacrylate.

#### Respiratory:

Respiratory equipment approved by NIOSH/MSHA for protection against organic vapors and dusts is necessary to avoid inhalation of excessive air contaminants. The appropriate respirator selection depends on the type and magnitude of exposure (refer 29 CFR 1910.134 for appropriate NIOSH approved respirators and to the NIOSH Pocket Guide to Chemical Hazards, DHHS (NIOSH) Publication NO. 2001-145 for equipment selection). Use a positive pressure air supplied respirator if there is a potential for an uncontrolled release, exposure levels are not known or under any other circumstances where air purifying respirators may not provide adequate protection.

#### Other Protective

#### Clothing/Equipment:

Emergency eye wash stations and safety showers should be available in the work area.

# Material Safety Data Sheet

MSDS Number: C6034F

Issue Date: 11/13/1985

Product Name: S-300, GPA, GPM, GPS, UVT

Revised Date: 12/15/2004

## Section 9 – Physical/Chemical Properties

**Appearance:** Solid sheet, various colors

**Boiling Point:** N/A

**Molecular/Chemical Formula:**  $(C_7H_{12}O_2 - C_5H_8O_2)_x$

**Evaporation Rate:** N/A

**Bulk Density:** N/A

**Freezing Point:** N/A

**Melting Point:** N/A

**Octanol/Water Partition Coefficient:** N/A

**Water/Oil Distribution Coefficient:** N/A

**Odor:** Odorless

**Odor Threshold:** N/A

**Percent Volatile:** N/A

**pH Value:** N/A

**Physical State:** Solid sheet

**Reactivity in Water:** N/A

**Solubility in Water:** N/A

**Specific Gravity or Density(Water=1):** N/A

**Vapor Density:** N/A

**Vapor Pressure:** N/A

## Section 10 – Stability/Reactivity

**Stability:**

Stable

**Conditions to Avoid:**

Temperatures above 500° F (260° C) can release methyl methacrylate.

**Incompatibility With Other Materials:**

None known.

**Hazardous Decomposition Products:**

Carbon dioxide, carbon monoxide, acrid smoke and fumes, possibly methyl methacrylate.

**Hazardous Polymerization:**

Will not occur

**Conditions to Avoid:**

None known.

# Material Safety Data Sheet

MSDS Number: C6034F

Issue Date: 11/13/1985

Product Name: S-300, GPA, GPM, GPS, UVT

Revised Date: 12/15/2004

## Section 11 – Toxicological Information

| VALUE | ANIMAL | ROUTES | COMPONENTS |
|-------|--------|--------|------------|
| N/A   | N/A    | N/A    | N/A        |

### Toxicological Information:

#### Product Based information:

No toxicological information is available for the finished product. This product is generally believed to be inert based on available data.

#### Ingredient Based Information:

The LD<sub>50</sub> for butyl acrylate, methyl methacrylate copolymer (CAS No. 25852-37-3) is greater than 29,500 mg/kg.

One of the monomers of butyl acrylate, methyl methacrylate copolymer, is methyl methacrylate (MMA). In one study, high doses of MMA were reported to produce an increased incidence of blood vessel aggregates in rat pups whose mothers received MMA by injection while pregnant.

Degenerative changes in the liver were observed in Guinea pigs following inhalation exposure to 9.5 ppm of MMA for 3 hours/day for 15 days, according to a 1945 report.

Ingestion of MMA caused irritation of the alimentary canal and kidney and liver lesions (Lefaus, R. Practical Toxicology of Plastics. CRC Press, Inc., 1968P.324). Methyl methacrylate has been shown to cause neurotoxic effects in primarily animal studies.

Carcinogenicity for Cadmium: Cadmium and Cadmium Compounds are listed as undifferentiated in IARC and the Annual NTP Report as carcinogenic to animals, but with only limited and conflicting evidence of carcinogenicity to humans. These listings are based on test results for Cadmium Compounds other than the pigmentary forms, which are not contained in this product (i.e., oxides and metals). Limited studies have suggested that human exposure to cadmium (primarily as the oxide) is associated with an increased risk of cancer. Various cadmium salts have been shown to cause local sarcomas, testicular atrophy (i.e., decreased size) and testicular tumors in laboratory animals following intravenous and subcutaneous injections.

**Possible target organs:** Skin and respiratory system (e.g., lungs)

### *Additional Information If Applicable*

## Section 12 – Ecological Information

### Ecological Information:

No ecological data are currently available.

### *Additional Information If Applicable*

# Material Safety Data Sheet

MSDS Number: C6034F

Issue Date: 11/13/1985

Product Name: S-300, GPA, GPM, GPS, UVT

Revised Date: 12/15/2004

## Section 13 – Disposal Considerations

**Disposal Considerations:** Dispose of in accordance with local, state and federal requirements. This product as sold in its marketed form is not considered an EPA hazardous waste when discarded.

**Additional Information If Applicable**

## Section 14 – Transport Information

**Proper Shipping Name:** Not regulated as a hazardous material

**Hazard Class:** none

**ID Number:** none

**Packing Group:** none

**Additional Information If Applicable**

## Section 15 – Regulatory Information

### U.S. Federal Regulations:

Toxic Substances Control Act (TSCA) Inventory- Yes

Superfund Amendments and Reauthorization Act (SARA 313)- Cadmium Compounds

### State Regulations:

California Proposition 65 List- Yes\*(Cadmium compounds)

\*Warning, this product contains chemical(s) known to the state of California to cause cancer and/or birth defects or other reproductive harm. The Proposition 65 chemical(s) found in this product appear in trace amounts and would not be expected to pose significant risk; however, a risk assessment for this (these) chemical(s) has not yet been performed. Each product should be assessed in light of its use.

### International Regulations:

European Inventory (EINECS)- Unknown

Canadian Inventory (DSL)- Yes

### SARA Hazards:

**Acute:** Yes

**Chronic:** Yes

**Reactive:** No

**Fire:** No

**Pressure:** No

**Additional Information If Applicable**

## Section 16 – Other Information

**NFPA Codes:**

**HMIS Codes:**

**Health:** 2

**Health:** 1

**Flammability:** 0

**Flammability:** 0

**Reactivity:** 0

**Reactivity:** 0

### Label Statements:

CAUTION! Inhalation of dusts or vapors may cause upper respiratory tract irritation with coughing and a

# Material Safety Data Sheet

MSDS Number: C6034F

Issue Date: 11/13/1985

Product Name: S-300, GPA, GPM, GPS, UVT

Revised Date: 12/15/2004

burning sensation in the throat. Repeated skin exposures to dusts may cause allergic skin reactions.  
Avoid contact with eyes, skin and clothing  
Avoid breathing dust or vapors.  
Wash thoroughly after handling.  
Launder contaminated clothing before re-use.  
Use only with adequate ventilation.  
If repeated skin contact may occur, wear PVA gloves.  
Wear chemical safety goggles.  
If Exposure Limits may be exceeded, wear NIOSH approved respirator with OV/N95 cartridges.

#### **Other Information:**

If you require additional information regarding any legal or regulatory requirements referred to in this MSDS, we suggest that you consult with an appropriate regulatory agency, or with a professional with expertise in this area.

This information is taken from sources or based upon data believed to be reliable; however, Aristech Acrylics LLC makes no warranty as to the absolute correctness or sufficiency of any of the foregoing or that additional or other measures may not be required under particular conditions.

#### **Additional Information If Applicable**

Reason for MSDS Revision: Additional product names added to MSDS  
This MSDS was prepared in accordance with the ANSI Z400.1 1993 Guideline for the Preparation of Material Safety Data Sheets.

#### **KEY**

N/A= Not Applicable  
MSHA=Mine Safety and Health Administration  
NIOSH=National Institute of Occupational Safety and Health  
SARA= Superfund Amendment and Reauthorization Act  
CNS= Central Nervous System  
ACGIH=American Conference of Governmental Industrial Hygienists  
OSHA=Occupational Safety and Health Administration  
PNOC=Particulates Not Otherwise Classifiable  
TLV=Threshold Limit Value  
PEL=Permissible Exposure Limit  
TWA=Time Weighted Average  
STEL=Short Term Exposure Limit  
CEIL=Ceiling Limit Value  
For additional product information, please call 800-354-9858.