

Safety Data Sheet

Stonefill Granite

MSDS No. 10040.14

Date of Preparation: 6/29/99

Revision: 7/19/13

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Stonefill Granite

General Use: Used in cultured marble applications.

Manufacturer: The R. J. Marshall Company
26776 W. 12 Mile Road
Southfield, MI 48034-7807
Phone: (248) 353-4100, Fax: (248) 948-6460

Emergency Phone: (800) 424-9300

Date Revised: 7/19/13

Prepared By: Stephanie Nichols

Section 2 - Hazards Identification

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Potential Health Effects

Warning: Irritant

Primary Entry Routes: Inhalation, Eye, and Ingestion.

Acute Effects

Inhalation: Inhalation of high concentrations of this inert nuisance particulate can result in mild irritation of the respiratory tract.

Eye: May cause irritation through mechanical abrasion.

Skin: May cause irritation through mechanical abrasion.

Ingestion: Unlikely.

Carcinogenicity: This product contains crystalline silica (quartz) as an impurity. Prolonged exposure to respirable crystalline silica dust concentrations exceeding occupational exposure limits may increase the risk of developing a disabling lung disease called silicosis. Crystalline silica is listed as a human carcinogen by IARC. This product is not listed as a carcinogen by OSHA, NTP, or IARC.

R-phrases: R36/37/38: Irritating to eyes, respiratory system, and skin.

HMIS

H 1

F 0

R 0

PPE† E

†Sec. 8

Section 3 - Composition / Information on Ingredients

Ingredient Name	CAS Number	Wt. %
Crystalline Silica	14808-60-7	0.75% max
Nuisance Dust	-----	100% max

Section 4 - First Aid Measures

Inhalation: If overcome by high dust concentrations, remove to a ventilated area. Seek medical attention for any symptoms that may develop.

Eye Contact: Flush eyes thoroughly for 15 minutes taking care to rinse under eyelids. Do not scrub. Abrasion may cause irritation. If discomfort continues, continue to wash with water. If irritation persists, consult a physician.

Skin Contact: Wash skin thoroughly with soap and water. Consult a physician if irritation persists.

Ingestion: Consult a physician.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Note to Physicians: n/a

Special Precautions/Procedures: n/a

Section 5 - Fire-Fighting Measures

Extinguishing Media: Water spray, carbon dioxide, or other dry chemical.

Unusual Fire or Explosion Hazards: None known.

Hazardous Combustion Products: May include carbon monoxide, carbon dioxide, smoke, oxides of nitrogen, and styrene.

Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face-piece operated in pressure-demand or positive-pressure mode.

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Collect solids. Recycle if possible.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Avoid generating dust during handling.

Storage Requirements: S-phrase: S8 Keep material dry.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Respiratory Protection: Wear dust mask if necessary.

Protective Clothing/Equipment: S-phrases: S37/39 Wear safety glasses and gloves. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Exposure Limits:

Ingredient	OSHA PEL		ACGIH TLV	
	TWA	STEL	TWA	STEL
Crystalline Silica	10 mg/m ³ respirable dust	none estab.	0.025 mg/m ³ respirable dust	none estab.
Nuisance Dust	15 mg/m ³ total dust 5 mg/m ³ respirable dust	none estab.	none estab.	none estab.

Section 9 - Physical and Chemical Properties

Physical State: powder

Appearance and Odor: Odorless, color varies

Odor Threshold: n/e

Vapor Pressure: n/a

Vapor Density (Air=1): n/a

Formula Weight: n/a

Density: n/e

Specific Gravity (H₂O=1, at 4 °C): 2.2-2.3

pH: n/e

Flash Point: n/a

Flash Point Method: n/a

Burning Rate: Not determined.

Water Solubility: slight

Other Solubilities: n/a

Boiling Point: n/a

Freezing/Melting Point: n/a

Viscosity: n/a

Refractive Index: n/a

Surface Tension: n/a

% Volatile: n/a

Evaporation Rate: n/e

Auto-ignition Temperature: Not determined.

Flammability Classification: Non-flammable.

Section 10 - Stability and Reactivity

Stability: This product is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: Strong acids or alkaline may destroy surface appearance.

Conditions to Avoid: none known.

Hazardous Decomposition Products: Thermal oxidative decomposition may produce carbon monoxide, carbon dioxide, smoke, oxides of nitrogen, and styrene.

Section 11- Toxicological Information

Toxicity Data:*

Eye Effects: Nuisance dust. May cause irritation through mechanical abrasion. Flush with water for at least 15 minutes. Consult physician if irritation is persistent.

Skin Effects: Nuisance dust. May cause irritation through mechanical abrasion. Wash skin thoroughly with soap and water.

Acute Inhalation Effects: Overexposure to dust may cause irritation to the respiratory tract. Should this occur, remove affected individual to fresh air. If symptoms persist, consult a physician.

Acute Oral Effects: None known.

Chronic Effects: Prolonged exposure to respirable crystalline silica dust concentrations exceeding occupational exposure limits may increase the risk of developing a disabling lung disease called silicosis.

Carcinogenicity: Crystalline silica is listed as a human carcinogen by IARC.

Section 12 - Ecological Information

No information available.

Section 13 - Disposal Considerations

Disposal: Recycle or landfill if possible. This substance is inert and does not require special disposal methods. Follow applicable Federal, state, and local regulations.

Section 14 - Transport Information

DOT Transportation Data (49 CFR 172.101): This product is not classified as dangerous under the transport regulations for road, rail, sea, or air transport.

Section 15 - Regulatory Information

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

RCRA Hazardous Waste Classification (40 CFR 261.??): Not classified

CERCLA Hazardous Substance (40 CFR 302.4) Not listed

SARA Toxic Chemical (40 CFR 372.65): Not listed

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed

Crystalline Silica is subject to the reporting requirements of California's Safe Drinking Water and Toxic Enforcement Act of 1986 ("Proposition 65").

OSHA Regulations:

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): Not listed

TSCA

This substance or all of its components are on the Chemical Substances Inventory of the Toxic Substance Control Act (TSCA Inventory [USA]). Please note that this product is not subject to any legal reporting requirements under these acts.

INTERNATIONAL REGULATIONS

This substance or all of its components are listed on the following inventories:

Australia: Listed on AICS

China: Listed on IECSC

Europe: Listed on EINECS

Japan: Listed on ENCS

Korea: Listed on ECL

New Zealand: Listed on NZIoC

Philippines: Listed on PICCS

Taiwan: Listed on NECI

Canada: Components are listed on either the DSL or NDSL

Section 16 - Other Information

Prepared By: Stephanie Nichols

Revision Notes: Added SFHD series

Product Grades Available from the R. J. Marshall Company (this list may be incomplete):

SFL 2000	SFL 3002	SFL 3350	SFL 3750	SFL 7230	SFHD2105	SFHD3365
SFL 2013	SFL 3040	SFL 3400	SFL 3900	SFL 7300	SFHD2340	SFHD3675
SFL 2015	SFL 3110	SFL 3430	SFL 4200	SFL 8000	SFHD2400	SFHD3825
SFL 2030	SFL 3221	SFL 3500	SFL 4300	SFL 8200	SFHD3010	SFHD3945
SFL 2100	SFL 3300	SFL 3600	SFL 6150		SFHD3150	SFHD4115
SFL 3000	SFL 3310	SFL 3630	SFL 6300	SFX 3500	SFHD3200	

Note: This includes all EXP SFL blends and all SFL special blends.

Disclaimer: Information contained herein is presented in good faith and is based on data believed to be accurate. However no warranty is expressed or implied regarding this information or the results obtained from the use of this Material Safety Data Sheet, whether it originates with The R. J. Marshall Company or others. This Safety Data Sheet relates only to the specific material designated herein. It does not relate to use with other material or processes. This information is supplied with the condition that the user will make appropriate determination as to its suitability for their purpose prior to using it.