

1 Identification

- **Product identifier**
- **Trade name:** P11 Type 1 Light Brown
- **Article number:** 1011288
- **Application of the substance / the mixture** Epoxy resin
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Company Name: Axson USA, Inc.

- Headquarters:
31200 Stephenson Hwy
Madison Heights, MI 48071
USA

- ehs-us@axson.com
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1(248) 588-2270
Chemtec 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Styrene
Talc (Mg₃H₂(SiO₃)₄)
cobalt bis(2-ethylhexanoate)

Trade name: P11 Type 1 Light Brown

(Contd. of page 1)

ethanol

Hazard statements

Flammable liquid and vapour.

Harmful if swallowed.

May cause cancer.

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If swallowed: Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

Rinse mouth.

In case of fire: Use for extinction: CO2, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 1

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = 1

Fire = 3

Reactivity = 0

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

CAS: 100-42-5	Styrene	10 - 20%
---------------	---------	----------

(Contd. on page 3)

Trade name: P11 Type 1 Light Brown

(Contd. of page 2)

CAS: 14807-96-6 EINECS: 238-877-9	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	10 - 20%
CAS: 112945-52-5	Fumed silica - untreated	1 - 5%
CAS: 64-17-5 EINECS: 200-578-6	ethanol	0.1-<1%
CAS: 136-52-7 EINECS: 205-250-6	cobalt bis(2-ethylhexanoate)	0.1-<1%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

Trade name: P11 Type 1 Light Brown

(Contd. of page 3)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect from heat.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

100-42-5 Styrene

ACGIH TLV Short-term value: 170 at 40 ppm mg/m³
Long-term value: 85 at 20 ppm mg/m³

OSHA PEL Long-term value: 100 ppm mg/m³
Ceiling limit value: 200 ppm mg/m³

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Trade name: P11 Type 1 Light Brown

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Thixotropic Paste

Color: Grey to tan

· Odor: Pungent

· Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 145 °C (293 °F)

· Flash point: 31 °C (88 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 490 °C (914 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower: 0.9 Vol %

Upper: 6.8 Vol %

· Vapor pressure at 20 °C (68 °F): 6 hPa (5 mm Hg)

· Density at 20 °C (68 °F): 1.35 g/cm³ (11.266 lbs/gal)

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

· Solvent content:

Organic solvents: 0.5 %

VOC content: 16.8 %

226.8 g/l / 1.89 lb/gl

(Contd. on page 6)

Trade name: P11 Type 1 Light Brown

(Contd. of page 5)

Solids content: 32.5 %
Other information No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

Oral	LD50	800-3100 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rabbit)

100-42-5 Styrene

Oral	LD50	316 mg/kg (mouse)
		2650 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	11.8 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc (Mg3H2(SiO3)4)	2B
64-17-5	ethanol	1
136-52-7	cobalt bis(2-ethylhexanoate)	2B
108-10-1	4-methylpentan-2-one	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

Trade name: P11 Type 1 Light Brown

(Contd. of page 6)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, IMDG, IATA	UN1866
· UN proper shipping name	
· DOT	Resin solution
· IMDG, IATA	RESIN SOLUTION
· Transport hazard class(es)	
· DOT, IMDG, IATA	
· Class	3 Flammable liquids
· Packing group	
· DOT, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· EMS Number:	F-E,S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

(Contd. on page 8)

Trade name: P11 Type 1 Light Brown

(Contd. of page 7)

· Transport/Additional information:

· DOT

· Quantity limitations

On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

· UN "Model Regulation":

UN1866, Resin solution, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

136-52-7 cobalt bis(2-ethylhexanoate)

108-10-1 4-methylpentan-2-one

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

108-10-1 4-methylpentan-2-one

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

64-17-5 ethanol

108-10-1 4-methylpentan-2-one

· Carcinogenic categories

· EPA (Environmental Protection Agency)

108-10-1 4-methylpentan-2-one

I

142-82-5 heptane

D

· TLV (Threshold Limit Value established by ACGIH)

14807-96-6 Talc (Mg3H2(SiO3)4)

A4

64-17-5 ethanol

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02



GHS07



GHS08

(Contd. on page 9)

Trade name: P11 Type 1 Light Brown

(Contd. of page 8)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Styrene

Talc (Mg₃H₂(SiO₃)₄)

cobalt bis(2-ethylhexanoate)

ethanol

· **Hazard statements**

Flammable liquid and vapour.

Harmful if swallowed.

May cause cancer.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If swallowed: Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

Rinse mouth.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 04/20/2015 / 5

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

(Contd. on page 10)



Safety Data Sheet
acc. to OSHA HCS

Printing date 04/20/2015

Reviewed on 04/20/2015

Trade name: P11 Type 1 Light Brown

Acute Tox. 4: Acute toxicity, Hazard Category 4
Carc. 1A: Carcinogenicity, Hazard Category 1A

(Contd. of page 9)

USA