



Safety Data Sheet

FOR INDUSTRIAL USE ONLY

YELLOW

Section 1. Product and company identification

Product Name: YELLOW

SDS Number: QUICKMIX (USE 944X064 BASE)
970YA038C

Product Use: Industrial

Manufacturer, Importer, Supplier: Polynt Composites USA, Inc.
99 East Cottage Avenue
Carpentersville IL 60110

Telephone: E-Mail: MSDS@pccrusa.com

For Emergency Transportation Information
CHEMTREC US Domestic (800) 424-9300
CHEMTREC International (703) 527-3887

For additional health and safety or regulatory information, call 1 847-836-3627.

Section 2. Hazard(s) identification

EMERGENCY OVERVIEW: May cause sensitization by inhalation and skin contact. Risk of serious damage to the lungs (by aspiration).

GHS Classification

Flam. Liq. 4

Symbol(s) of Product

No GHS Symbols Exist

Signal Word

Warning

GHS HAZARD STATEMENTS

Flammable liquid, category 4 H227 Combustible liquid.

GHS LABEL PRECAUTIONARY STATEMENTS

P202 Do not handle until all safety precautions have been read and understood.
 P233 Keep container tightly closed.
 P281 Use personal protective equipment as required.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container to in accordance with local/regional/national/international regulations.

Section 3. Composition/Information on ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
TITANIUM DIOXIDE	13463-67-7	10 - 20	No Information	No Information
DIETHYLENE GLYCOL	111-46-6	1.0-5.0	No Information	No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

Section 4. First-aid measures



FIRST AID - EYE CONTACT: If symptoms persist, call a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

FIRST AID - INGESTION: Aspiration hazard if swallowed - can enter lungs and cause damage. If ingested, consult a physician. Do NOT induce vomiting.

FIRST AID - INHALATION: Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effect, such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Give oxygen or artificial respiration if needed. Move to fresh air in case of accidental inhalation of vapours. Remove person to fresh air. If signs/symptoms continue, get medical attention.

FIRST AID - SKIN CONTACT: Wash contaminated clothing before reuse. Wash skin with soap and water for several minutes. Get medical attention if irritation develops. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Prolonged skin contact may defat the skin and produce dermatitis.

Section 5. Fire-fighting measures

Extinguishing Media:

Suitable Carbon Dioxide, Dry Chemical, Foam, Water Fog
Not suitable Water Jet

SPECIAL FIREFIGHTING PROCEDURES: Use full protective clothing. Use a properly-fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Water spray. Dry powder. Carbon dioxide (CO₂). Do not use a solid water stream as it may scatter and spread fire. Cool containers / tanks with water spray. Vapors may be ignited by heat, pilot lights, other flames and ignition sources. Self-accelerating decomposition may occur if the specific control temperature is not maintained. Vapors may accumulate in confined areas (basement, tanks, hopper/tank cars, etc.).

UNUSUAL FIRE AND EXPLOSION HAZARDS: No Information

Section 6. Accidental release measures

ENVIRONMENTAL MEASURES: Prevent entry into waterways, sewers, basements or confined areas. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Avoid breathing vapors or mists. Use non-sparking tools and equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. Do not flush into surface water or sanitary sewer system. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

PRECAUTIONARY MEASURES: No Information

Section 7. Handling and storage



HANDLING: Avoid contact with skin, eyes and clothing. Ground/bond container and equipment. Wear personal protective equipment. Use only in well-ventilated areas. Keep away from heat and sources of ignition. Do not breathe vapors, mist or gas.

STORAGE: Store contents under 100F (37.8C). Store drums with bung in the upright position. Electrical equipment must be grounded; suitable for the classification of the area where it is installed and conform to the National Electric Code (see NFPA 70). Keep container closed when not in use. Store and dispose according to national, state and local regulations.

HYGIENIC PRACTICES: When using, do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing. General

industrial hygiene practice. Wash hands before eating, drinking, or smoking.

WORK PRACTICES: Put on appropriate personal protective equipment. Wash hands after handling chemicals and before eating, drinking, or smoking. Read and understand entire SDS before handling chemical.

SPECIAL HANDLING PROCEDURES: Put on appropriate personal protective equipment. Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use.

Section 8. Exposure controls/personal protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA CEILING</u>
TITANIUM DIOXIDE	10 mg/m ³	N.E.	15 mg/m ³	N.E.
DIETHYLENE GLYCOL	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: When concentrations exceed the exposure limits specified, use of a NIOSH-approved dust, mist and fume respirator is recommended. Where the protection factor of the respirator may be exceeded, use of a full facepiece, supplied air, or Self Contained Breathing Apparatus (SCBA) may be necessary. Use a properly-fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.



SKIN PROTECTION: Wear suitable protective equipment. Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.



EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses with side-shields. Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.



OTHER PROTECTIVE EQUIPMENT: Use good hygiene practices. Wash face and hands before eating, drinking, and smoking. Eye wash and safety showers should be readily available.



HYGIENIC PRACTICES: When using, do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing. General industrial hygiene practice. Wash hands before eating, drinking, or smoking.

Section 9. Physical and chemical properties

Color:	Yellow	Physical State:	Liquid
Odor:	Moderate aromatic	Odor Threshold:	Not Available
Density, g/cm³:	1.466	pH:	Not Available
Freeze Point, °C:	Not Available	Viscosity:	Not Available
Solubility in Water:	Insoluble	Partition Coefficient, n-octanol/ water:	Not Available
Decomposition Temp., °C:	Not Available	Flash Point, °C / F°	93 / 199
Boiling Range, °C:	0	Explosive Limits, vol%:	Not Available
Vapor Pressure:	Not Available	Auto-ignition Temp., °C:	Not Available

(See "Other information" Section for abbreviation legend)

Section 10. Stability and reactivity

STABILITY: The product is normally supplied in a stabilized form. The permissible storage period and/or storage temperature is

noticeably exceeded, the product may polymerise with heat evolution. Stable under normal conditions.

CONDITIONS TO AVOID: Avoid improper addition of promotor and/or catalyst. Avoid direct contact of MEKP catalyst with accelerator. If adding accelerator like cobalt drier, mix accelerator with base material before adding catalyst. Burning may produce obnoxious and toxic fumes. Hazardous polymerization may occur. Keep product away from heat, sparks, pilot lights, static electricity, and open flame.

INCOMPATIBILITY: Aluminium. Free radical initiators. Bases. Copper. Strong acids. Strong acids, strong bases, strong oxidizing agents. Strong oxidizing and reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: None under normal use.

Section 11. Toxicological information



Practical Experiences

EFFECT OF OVEREXPOSURE - EYE CONTACT: Presumed to be moderately irritating to the eyes. Exposure may cause mild irritation. Symptoms may include stinging, tearing, and redness.

EFFECT OF OVEREXPOSURE - INGESTION: May cause severe gastrointestinal disturbance with headache, nausea, vomiting and diarrhea.

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes). Prolonged, repeated or high exposures may cause central nervous system depression leading to headaches, nausea, drowsiness, dizziness, and possibly narcosis. In extreme cases, may cause loss of consciousness. Ingestion of large doses may cause headaches, dizziness, nausea, vomiting, and drowsiness. Irritating to skin.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Repeated or prolonged exposure may cause central nervous system damage. Prolonged skin contact may defat the skin and produce dermatitis. Prolonged or repeated exposure may cause liver and kidney effects.

CARCINOGENICITY: This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
13463-67-7	TITANIUM DIOXIDE	>10000 mg/kg Rat	N.I.	N.I.
111-46-6	DIETHYLENE GLYCOL	12565 mg/kg Rat	11890 mg/kg Rabbit	N.I.

N.I. - No Information

Section 12. Ecological information

ECOLOGICAL INFORMATION: Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits. Discharge into the environment must be avoided.

Section 13. Disposal considerations



DISPOSAL METHOD: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should always comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers.

Section 14. Transport information

SPECIAL TRANSPORT PRECAUTIONS: No Information

International transport regulations

Regulatory Information:	UN/NA Number	Proper Shipping Name	Classes/ *PG	Reportable Quantity (RQ)
CFR		Not regulated		
IMO/IMDG		Not regulated		
IATA		Not regulated		

Section 15. Regulatory information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

<u>Chemical Name</u>	<u>CAS-No.</u>
BENZOIC ACID	65-85-0

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
ALUMINA (ALUMINUM OXIDE)	1344-28-1

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following hazardous materials are listed.

<u>Chemical Name</u>	<u>CAS-No.</u>
TITANIUM DIOXIDE	13463-67-7
STYRENE MONOMER	100-42-5
HYDROQUINONE	123-31-9
ISOPROPYL ALCOHOL	67-63-0
MINERAL SPIRITS	8032-32-4
4-METHOXYPHENOL	150-76-5
ETHYLBENZENE	100-41-4

PENNSYLVANIA RIGHT-TO-KNOW

The following hazardous ingredients are present:

<u>Chemical Name</u>	<u>CAS-No.</u>
TITANIUM DIOXIDE	13463-67-7
DIETHYLENE GLYCOL	111-46-6
STYRENE MONOMER	100-42-5
HYDROQUINONE	123-31-9
ISOPROPYL ALCOHOL	67-63-0
MINERAL SPIRITS	8032-32-4
4-METHOXYPHENOL	150-76-5
ETHYLBENZENE	100-41-4

U.S. State Regulations:**MASSACHUSETTS RIGHT-TO-KNOW:**

The following hazardous materials are listed.

<u>Chemical Name</u>	<u>CAS-No.</u>
TITANIUM DIOXIDE	13463-67-7
STYRENE MONOMER	100-42-5
HYDROQUINONE	123-31-9
ISOPROPYL ALCOHOL	67-63-0
4-METHOXYPHENOL	150-76-5
ETHYLBENZENE	100-41-4

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
TITANIUM DIOXIDE	13463-67-7
ETHYLBENZENE	100-41-4

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations**CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class: No Information

Chemical Inventories	Australia inventory (AICS)	Not Determined
	Canada inventory (DSL)	Not Determined
	Japan Inventory (ENCSC)	Not Determined
	China Inventory (IECSC)	Not Determined
	Korea Inventory (KECI)	Not Determined
	New Zealand (NZIoC)	Not Determined
	Philippines (PICCS)	Not Determined
	United States Inventory (TSCA 8b)	All components are listed or exempted

Section 16. Other information, including date of preparation of the last revision

Revision Date:	11/23/2015	Supersedes Date:	New SDS
Reason for revision:	No Information		
Datasheet produced by:	Regulatory Department		

HMIS Ratings:

Health:	2*	Flammability:	2	Reactivity:	0	Personal Protection:	N.I.	Chronic Rating:	*
----------------	----	----------------------	---	--------------------	---	-----------------------------	------	------------------------	---

Volatile Organic Compounds, gr/ltr: Not Determined

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

No GHS Pictograms exist for Section 3

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information provided herein was believed by Polynt Composites USA, Inc. to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Polynt Composites USA, Inc. are subject to Polynt Composites USA, Inc terms and conditions of sale. Polynt Composites USA, Inc. MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY Polynt Composites USA, Inc, except that the product shall conform to Polynt Composites USA, Inc. specifications. Nothing contained herein constitutes an offer for the sale of any product.