

Safety Data Sheet

1. Product and Company Identification

Product name:

TrueVIS INK, TR-WH

Manufacture:

Roland DG Corporation

Address:

1-6-4 Shinmiyakoda, Kita-ku, Hamamatsu-shi,
Shizuoka-ken, 431-2103
JAPAN

Phone:

+ 81-53-484-1224

Fax:

+ 81-53-484-1226

Importer/Supplier:

Roland DGA Corporation

Address:

15363 Barranca Parkway Irvine, CA 92618-2201
U.S.A.

Phone:

949-727-2100

Fax:

949-727-2112

Emergency telephone:

949-727-2100

Use of the product:

Inkjet Printing

Date of issue:

26 February, 2016

2. Hazard Identification

2.1 Emergency Overview:

Appearance and odor:

White liquid and slight odor

This product is classified as dangerous according to GHS.

Flammable liquids

Category 4

Acute toxicity - oral

Category 5

Skin corrosion/irritation

Category 2

Eye damage/irritation

Category 1

GHS label elements, including precautionary statements

Pictogram



Signal word(s)

Danger

Hazard statement(s)

Combustible liquid.
May be harmful if swallowed.
Causes skin irritation.
Causes serious eye damage.

Contains methyl methacrylate. May produce an allergic reaction.

Precautionary statement(s)	
Prevention	Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Wear protective gloves/protective clothing/eye protection/face protection.
Response	IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician if you feel unwell.
Storage	Store in a well-ventilated place. Keep cool.

2.2. OSHA regulatory status

This product is considered hazardous material by the OSHA Communication Standard (29 CFR 1910.1200)

2.3. Other hazards

Potential Health Effects:

Eyes:	Causes severe eye injury which may persist for several days.
Skin:	Contact with skin may cause irritation, swelling or redness.
Inhalation:	Exposure to vapors (mist) will cause respiratory irritation and anesthesia.
Ingestion:	May cause upset stomach.
Chronic Health Hazards:	None Known.
Carcinogenicity:	The product contains Titanium dioxide. IARC evaluated printing ink as a Group3(Not classifiable as to carcinogenicity to humans).

See section 11 for more information.

2.4. Potential environmental effects

See section 12 for Ecological information.

3. Composition/Information on Ingredients

Composition	CAS No.	% By Weight	Classification HCS
Diethylene glycol diethyl ether	112-36-7	60-70	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	5-15	Acute Tox. 4: H302 Eye Dam. 1: H318 STOT SE 3: H336
Titanium dioxide	-	10-20	Not classified as hazardous
Methyl methacrylate	80-62-6	<0.3	Flam. Liq. 2: H225 STOT SE 3: H335 Skin Irrit. 2: H315 Skin Sens. 1: H317

4. First Aid Measures

4.1. First aid procedures

Eyes:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Hold eyelids open during flushing. Call a physician.
Skin:	In case of contact, immediately flush with plenty of water while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.
Ingestion:	If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Note to physicians

May cause skin and eye irritation. Excessive inhalation of mist will cause respiratory irritation.

5. Fire Fighting Measures

5.1. Flammable properties:

Combustible liquid under Hazard Communication Standard (HCS, U.S.A).

Flash Point: 71 deg.C

5.2. Extinguishing media

Suitable extinguishing media:

Powders, bubbles, carbon dioxide, dry sand, water, reinforcement liquid

Unsuitable extinguishing media:

No information

5.3. Protection of fire fighters

Special hazards arising from the substance or mixture

Toxic and irritating fume and/or gases may generate by combustion.

Protective equipment and precautions for firefighters

Wear self-contained breathing apparatus (SCBA) and full protective equipment.

Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental Release Measures

General:

Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill. Absorb spill with sand or earth then place in a chemical waste container.

6.1. Personal precautions

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods for containment

Dike spilled product.

6.4. Methods for Clean-up

Sweep up material and dispose as waste following local regulations. Scrub contaminated area with detergent and water.

6.5. Other information

No information

6.6. Spill or leak statements by type of chemical

Eliminate all ignition sources. Use appropriate personal protective equipment (PPE). Absorb and/or contain spill with inert sand, then place in suitable container. For large spills; use water spray to disperse vapors and dilute spill to a nonflammable mixture. Do not flush to sewer. Prevent run-off from entering drains, sewers or waterways.

7. Handling And Storage

7.1. Handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Keep out of reach of children and do not drink. Do not dismantle container. Make sure pouch is dry before insertion into printer housing.

7.2. Storage

Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with oxidizing agents or explosives.

8. Exposure Controls/Personal Protection

8.1. Exposure Guidelines

Occupational Exposure Limits:

EU:

components	TWA	STEL
Methyl methacrylate	50ppm	100ppm

DNEL(Derived No Effect Level)

components	Long term exposure	Short term exposure
Diethylene glycol diethyl ether	50.05mg/m ³	-
γ-butyrolactone	130mg/m ³	958mg/m ³

REACH Toxicological Information (Workers - Hazard via inhalation route)

US:

components	OSHA:PEL	ACGIH:TLV
Titanium dioxide	15mg/m ³ * *for total dust	3.5mg/m ³
Methyl methacrylate	100ppm 416mg/m ³	-

California OELs (California Code of Regulations, Title 8, Section 5155. Airborne Contaminants)

components	PEL	STEL
Diethylene glycol diethyl ether	5ppm, 33mg/m ³	-
Methyl methacrylate	50ppm, 205mg/m ³	100ppm, 410mg/m ³

Australia: OELs

components	TWA
Titanium dioxide	10mg/m ³
Methyl methacrylate	208 mg/m ³

8.2. Engineering controls

Provide general and/or local exhaust ventilation.

8.3. Personal protective equipment (PPE)

- Respiratory protection: In case ventilation is insufficient, wear respiratory protection. Use a half facepiece respirator (with goggles) or full face-piece respirator (without goggles) filtered with organic vapor pouch.
- Hand protection: Not required under suitable use as setting the pouch on the printer. However, in case of direct contact to ink, use protective gloves. Recommended impervious gloves is butyl rubber glove.
- Eye protection: Not required under suitable use as setting the pouch on the printer. However, in case of direct contact to ink, wear safety glasses or chemical splash goggles.
- Skin protection: Not required under suitable use as setting the pouch on the printer. However, in case of direct contact to ink, wear protective clothing.
- General hygiene measures: Wash hands after handling. In case contact with clothing, wash before reuse. Do not eat, drink or smoke in handling or storage area.

9. Physical and Chemical Properties

- Appearance: White Liquid
- Odor: Slightly
- pH: No data available
- Boiling point: No data available
- Flash point: 71 deg.C
- Flammability(solid,gas): Not applicable
- Explosive properties: No data available
- Oxidizing properties: None
- Vapor pressure: No data available
- Specific Gravity (g/cm³, 20°C) No data available
- Solubility: No data available
- Water Solubility: Lightly soluble
- Partition coefficient: n-octanol/water: No data available
- Viscosity: No data available
- Vapor density: No data available
- Evaporation rate: No data available
- Melting point: No data available
- Volatile organic compounds (VOC) content: 900 gram/liter (maximum value)

9.2. Other information: No information

10. Stability and Reactivity

- 10.1. Reactivity: Stable under normal temperature
- 10.2. Possibility of hazardous reactions: No data available
- 10.3. Chemical stability: Physically stable under an ambient temperature or lower.
- 10.4. Conditions to avoid: If it is heated, the container could explode to be broken down. Do not subject the container to static electricity.
- 10.5. Incompatible materials: This product should not mix with strong oxidants and high-pressure gases.
- 10.6. Hazardous decomposition products: Toxic gases such as CO and NOx will be generated during combustion.

11. Toxicological Information

Acute toxicity:	Diethylene glycol diethyl ether	
	LD50 (oral-rat)	4790 mg/kg
	LD50 (skin-rat)	No data available
	γ -butyrolactone	
	LD50 (oral-rat)	1580 mg/kg
	LD50 (skin-marmot)	5600 mg/kg
Skin corrosion/irritation:	No data available	
	Causes skin irritation. (Diethylene glycol diethyl ether)	
Serious eye damage/eye irritation:	No data available	
	Causes serious eye damage. (γ -butyrolactone)	
Respiratory or skin sensitisation:	No data available	
Germ cell mutagenicity:	No data available	
Reproductive toxicity:	No data available	
Carcinogenicity:	The product contains Carbon black. IARC evaluated printing ink as a Group3(Not classifiable as to carcinogenicity to humans).	
STOT-single exposure:	No data available	
STOT-repeated exposure:	No data available	
Aspiration hazard:	No data available	

12. Ecological Information

Ecotoxicity:	No data available
Persistence/Degradability:	No data available
Bioaccumulation/Accumulation:	No data available
Mobility in environment media:	No data available
Other adverse effects:	No data available

13. Disposal Considerations

Treatment, storage, transportation and disposal must be in accordance with applicable federal, state/provincial, and local regulations. Do not flush to surface water or sanitary sewer system.

14. Transport Information

14.1. UN Class/UN Number:	
ADR/ADG/DOT, IMDG, or IATA :	Not regulated
14.2. UN proper shipping name:	
ADR/ADG/DOT, IMDG, or IATA :	Not regulated
14.3. Transport hazard class(es):	
ADR/ADG/DOT, IMDG, or IATA :	Not regulated
14.4. Packing group:	
ADR/ADG/DOT, IMDG, or IATA :	Not regulated
14.5. Environmental hazards:	
ADR/ADG/DOT, IMDG, or IATA :	Not regulated
14.6. Special precautions for user:	Transport and storage of the product in accordance with general precautions and instructions mentioned in this SDS.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and IBC code:	Not regulated

15. Regulatory Information

EU Information:

Chemical Safety Assessment according to (EC)1907/2006:

This product has not carried out any Chemical Safety Assessment yet.

US Information:

Toxic Substances Control Act (TSCA): All ingredients are listed on the TSCA Inventory.

Product contains Diethylene glycol diethyl ether that is subject to TSCA Section 5 SNUR and to TSCA Section 12(b) export notification requirements.

California Proposition 65: Not regulated

SARA TITLE III:

Section 313:

Diethylene glycol diethyl ether (Chemical Category N230)

Triethylene glycol monobutyl ether (Chemical Category N230)

Australia Information:

Hazardous statement: Classified as hazardous according to NOHSC criteria.

16. Other Information

NFPA 704: Hazard Rating System

Health - 3 , Flammable - 2 , Reactivity - 0

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and experience is gained. Roland DG does not warrant the completeness or accuracy of the information contained herein.