

# MSDS Material Safety Data Sheet

## Quill Hair & Ferrule LTD



### Q-PRIM MP2054 WASH PRIMER

MSDS Number: P0076

Revision Date: 01/01/12

Page 1 of 5

## 1 PRODUCT AND COMPANY IDENTIFICATION

### Manufacturer

Quill Hair & Ferrule LTD  
1 Greengate Park Rd.  
P.O. Box 23927  
Columbia, SC 29224

Contact: Deborah Millar  
Telephone Number: 1-803-788-4499  
FAX Number: 1-803-736-4731  
E-Mail: DMiller@paint-info.com  
Web www.qhfonline.com

Product Name: Q-PRIM MP2054 WASH PRIMER  
Revision Date: 01/01/12  
MSDS Number: P0076  
Common Name: Undercoat  
Product Code: QPRIM MP2054  
Chemical Formula: Complex Mixture  
Product Use: Undercoat

24 Hours Emergency Number 1-800-451-8346

## 2 HAZARDS IDENTIFICATION

Route of Entry: Eyes; Ingestion; Inhalation; Skin  
Target Organs: Eyes; Skin; Respiratory system; Central nervous system; Hematopoietic system; Blood; Kidneys; Liver; Lymphoid system  
Inhalation: Anesthetic, may cause respiratory irritation and CNS depression. Can cause irritation and inflammation of the respiratory tract. Minimal respiratory tract irritation may occur with exposure to a large amount of material.  
Skin Contact: May cause irritation, tearing and redness.  
Eye Contact: May cause irritation.  
Ingestion: Aspiration hazard: Harmful or fatal if swallowed.

HMIS II-ratings (scale 0-4): Health = 2, Fire = 3, Reactivity = 0

HMIS® Rating H2/F3/PH0

NFPA-ratings (scale 0-4): Health = 2, Fire = 3, Reactivity = 0

## 3 COMPOSITION/INFORMATION ON INGREDIENTS

### Ingredients:

Cas #	Perc.	Chemical Name	ACGIH TLV (PPM)	OSHA PEL (PPM)
71-36-3	15-20%	n-Butyl alcohol	20	100
67-63-0	45-50%	Isopropanol	200	400
13530-65-9	5-10%	Zinc Chromate	10.0 ug/m3	.1 mg/m
108-10-1	5-10%	Methylisobutyl ketone	100	50
78-93-3	5-10%	Methyl ethyl ketone	200	200

# MSDS Material Safety Data Sheet

Quill Hair & Ferrule LTD



## Q-PRIM MP2054 WASH PRIMER

MSDS Number: P0076

Revision Date: 01/01/12

Page 2 of 5

### 4 FIRST AID MEASURES

**Inhalation:** If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.  
**Skin Contact:** Promptly flush skin with water until all chemical is removed. Get medical attention if needed.  
**Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Get immediate medical attention.  
**Ingestion:** Get prompt, qualified medical attention. Seek immediate medical attention. Induce vomiting.

### 5 FIRE FIGHTING MEASURES

**Flash Point:** 44 DEGREES F  
**LEL:** 1.2%  
**UEL:** 12.0%  
**Flammability Classification:** NFPA Class 1B flammable liquid

Dry powder, water spray, dry chemical, carbon dioxide, alcohol foam. Do not use a solid stream of water since the stream will scatter and spread the fire. Water spray may be used to keep fire exposed containers cool, dilute spills to nonflammable mixtures, protect personnel attempting to stop leak and disperse vapors.

### 6 ACCIDENTAL RELEASE MEASURES

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Absorb spill with inert material, then place in chemical waste container. Remove/Dispose of in a manner consistent with federal and local law. Do not use combustible materials, such as saw dust. Do not flush to sewer. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect attempting to stop leak and to flush spills away from exposures.

### 7 HANDLING AND STORAGE

**Handling Precautions:** Protect against physical damage.  
**Storage Requirements:** Store in a cool dry well ventilated area. Keep away from heat and flame. Do not get in eyes, on skin, or on clothing. Protect against physical damage. Outside or detached storage is preferred. Separate from oxidizing materials. Containers should be bonded and grounded from transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Containers of the material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** N/A  
**Protective Equipment:** HMIS PP, D | Face Shield and Eye Protection, Gloves, Apron  
Wear appropriate respirator when ventilation is inadequate or when spraying

### 9 PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Green liquid.  
**Physical State:** Liquid  
**Boiling Point:** 237F - 284F  
**Odor:** Faint ethereal & sweetish  
**Freezing/Melting Pt.:** N/A

# MSDS Material Safety Data Sheet

## Quill Hair & Ferrule LTD



### Q-PRIM MP2054 WASH PRIMER

MSDS Number: P0076

Revision Date: 01/01/12

Page 3 of 5

pH:	odor.	Solubility:	Slight
Vapor Pressure:	N/A	Spec Grav./Density:	.88
Vapor Density:	N/A		
VOC:	723.2 GRAMS PER/LITER	6.03 LBS PER GALLON	
Evap. Rate:	SLOWER THAN ETHER		
Percent Volatile:	82%		

## 10 STABILITY AND REACTIVITY

**Stability:** Product is stable under normal conditions.

**Conditions to avoid:** Oxidation promoting conditions ( Heat, Sunlight and Air), and high temperature

**Materials to avoid (incompatibility):** Strong Oxidizing Agents, alkalies, may attack metallic aluminum at high temperature

**Hazardous Decomposition products:** Carbon dioxide, peroxides, carbon monoxide

**Hazardous Polymerization:** Will not occur.

## 11 TOXICOLOGICAL INFORMATION

ACUTE TOXICITY				
Ingredient Name	Test	Results	Route	Species
n-Butyl alcohol	LD 50	2.5 g/kg	Oral	Rat
	LC 50	8000 ppm / four hours	Inhalation	Rat
	LD 50	> 10 ml/kg	Dermal	Rabbit
Isopropanol	LD 50	>2000 mg/kg	Oral	Rat
	LC 50	>5000 ppm/ one hour	Inhalation	Rat
	LD 50	>2000 mg/kg	Dermal	Rabbit
Zinc Chromate	LD 50	N/A	Oral	Rat
	LC 50	N/A	Inhalation	Rat
	LD 50	N/A	Dermal	Rabbit
Methyl isobutyl Ketone	LD 50	2080 mg/kg	Oral	Rat
	LC 50	>2000 ppm/four hours	Inhalation	Rat
	LD 50	20 ml/kg	Dermal	Rabbit
Methyl ethyl Ketone	LD 50	>2000 mg/kg	Oral	Rat
	LC 50	>5000 ppm/ one hour	Inhalation	Rat
	LD 50	>2000 mg/kg	Dermal	Rabbit

# MSDS Material Safety Data Sheet

Quill Hair & Ferrule LTD



## Q-PRIM MP2054 WASH PRIMER

MSDS Number: P0076

Revision Date: 01/01/12

Page 4 of 5

### 12 ECOLOGICAL INFORMATION

Environmental Fate: When released into the soil, this material is not expected to evaporate significantly. When released into the soil, this material may leach into groundwater. When released into the soil, this material may biodegrade to a moderate extent. When released into water, this material is not expected to evaporate significantly. When released into water, this material may biodegrade to a moderate extent. This material has an estimated bioconcentration factor (BCF) of less than 100. This material is not expected to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals, When released into the air, this material is expected to have the half-life of less than one day.

### 13 DISPOSAL CONSIDERATIONS

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

### 14 TRANSPORT INFORMATION

DOT Class: Flammable Liquid (3) #3

DOT:Paint Related Material, 3, UN1263, PG II

IATA:Paint Related Material, 3, UN1263, PG II

MULTI-MODAL:Paint Related Material, 3, UN1263, PG II

### 15 REGULATORY INFORMATION

\*n-Butyl alcohol (71-36-3 13%) CERCLA, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TXAIR, TXHWL

\*Isopropanol (67-63-0 45-50%) MASS, NJHS, NRC, OSHAWAC, PA, SARA313, TXAIR

\*Zinc Chromate (13530-65-9 7.83%) CERCLA, CSWHS, EPCRAWPC, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL, PROP 65, NRC

\*Methyl isobutyl ketone (108-10-1 15.9%) CERCLA, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

\*Methyl Ethyl Ketone (78-93-3 5%-10%) CERCLA, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

#### REGULATORY KEY DESCRIPTIONS

HAP = Hazardous Air Pollutants  
MASS = MA Massachusetts Hazardous Substances List  
OSHAWAC = OSHA workplace Air Contaminants  
PA = PA Right-To-Know List of Hazardous Substances  
TXAIR = TX Air Contaminants with Health Effects Screening Level  
CERCLA = Superfund clean up substance  
CSWHS = Clean water Act Hazardous substances  
EPCRAWPC = EPCRA water Priority Chemicals  
NJHS = NJ Extraordinarily Hazardous Substances  
NJHS = NJ Right-to-Know Hazardous Substances  
NRC = Nationally Recognized Carcinogens  
OSHAHTS = OSHA Hazardous and Toxic Substances

# MSDS Material Safety Data Sheet

**Quill Hair & Ferrule LTD**



---

## Q-PRIM MP2054 WASH PRIMER

MSDS Number: P0076

Revision Date: 01/01/12

Page 5 of 5

OSHAPSM = OSHA Chemicals Requiring process safety management  
PROP65 = CA Prop 65  
SARA313 = SARA 313 Title III Toxic Chemicals  
TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List)  
TXHWL = TX Hazardous Waste List  
HWRCRA = RCRA Hazardous Wastes  
PRIPOL = Clean Water Act Priority Pollutants  
TOXICPOL = Clean Water Act Toxic Pollutants  
TSCA = Toxic Substances Control Act

---

**16**

### OTHER INFORMATION

Quill Hair & Ferrule LTD believes that the data contained herein is accurate and derived from qualified sources. The data is not to be taken as a warranty or representation for which Quill Hair & Ferrule LTD assumes legal responsibility. It is offered solely for your consideration, investigation, and verification. Any use of this data and information should be determined by the end user in accordance with Federal, State and local laws and regulations.

---

**END OF MSDS DOCUMENT**