

# MSDS Material Safety Data Sheet

Quill Hair & Ferrule LTD



## Q-COAT DC MIXED COLOR

MSDS Number: P0056

Revision Date: 06/01/10

Page 1 of 7

### 1 PRODUCT AND COMPANY IDENTIFICATION

#### Manufacturer

Quill Hair & Ferrule LTD  
1 Greengate Park Rd.  
P.O. Box 23927  
Columbia, SC 29224

Contact: Ryan Jones  
Telephone Number: 1-803-788-4499  
FAX Number: 1-803-736-4731  
E-Mail: RyanJ@paint-info.com  
Web www.qhfonline.com

Product Name: Q-COAT DC MIXED COLOR  
Revision Date: 06/01/10  
MSDS Number: P0056  
Common Name: Topcoat  
Chemical Formula: CONTAINS QCOLR #  
Product Use: Topcoat

24 Hours Emergency Number 1-800-451-8346

### 2 HAZARDS IDENTIFICATION

Route of Entry: Eyes; Ingestion; Inhalation; Skin  
Target Organs: Eyes; Skin; Respiratory system; Central nervous system; Hematopoietic system; Blood; Kidneys; Liver; Lymphoid system  
Inhalation: Anesthetic, may cause respiratory irritation and CNS depression. Can cause irritation and inflammation of the respiratory tract. Minimal respiratory tract irritation may occur with exposure to a large amount of material.  
Skin Contact: May cause irritation, tearing and redness.  
Eye Contact: May cause irritation.  
Ingestion: Aspiration hazard: Harmful or fatal if swallowed.

HMIS II-ratings (scale 0-4): Health = 1, Fire = 3, Reactivity = 0  
HMIS® Rating H1/F3/PH0  
NFPA-ratings (scale 0-4): Health = 1, Fire = 3, Reactivity = 0

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

#### Ingredients:

Cas #	Perc.	Chemical Name	Colorant	ACGIH TLV (PPM)	OSHA PEL (PPM)
-----					
All contain the following					
107-98-2	45-60%	Propylene glycol methyl ether		100	100
111-76-2	10-20%	Glycol Ether EB		20	50
37631-86-9	0-10%	Silica, amorphous		10mg/m3	6mg/m3
The following colorants contain					
		Proprietary Ingredient	02	N/A	N/A

# MSDS Material Safety Data Sheet

## Quill Hair & Ferrule LTD



### Q-COAT DC MIXED COLOR

MSDS Number: P0056

Revision Date: 06/01/10

Page 2 of 7

NJTSR#678290-00-2-7441-P	PCP	02	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7442-P	PCP	06	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7398-P	PCP	06	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7399-P	PCP	06	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7535-P	PCP	08	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7412-P	PCP	08	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7413-P	PCP	12	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7431-P	PCP	12	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7432-P	PCP	16	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7429-P	PCP	16	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7430-P	PCP	18,20	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7435-P	PCP	18,20	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7436-P	PCP	22	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7396-P	PCP	22	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7397-P	PCP	24	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7408-P	PCP	24	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7409-P	PCP	26	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7394-P	PCP	26	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7395-P	PCP	28	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7392-P	PCP	28	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7393-P	PCP	30	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7425-P	PCP	30	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7426-P	PCP	32	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7427-P	PCP	32	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7428-P	PCP	36	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7421-P	PCP	36	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7422-P	PCP	38	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7477-P	PCP	38	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7478-P	PCP	40	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7475-P	PCP	40	N/A	N/A
Proprietary Ingredient				
NJTSR#678290-00-2-7476-P	PCP	42	N/A	N/A
Proprietary Ingredient				

# MSDS Material Safety Data Sheet

## Quill Hair & Ferrule LTD



### Q-COAT DC MIXED COLOR

MSDS Number: P0056

Revision Date: 06/01/10

Page 3 of 7

		NJTSR#678290-00-2-7437-P PCP			
		Proprietary Ingredient	42	N/A	N/A
		NJTSR#678290-00-2-7438-P PCP			
		Proprietary Ingredient	42	N/A	N/A
		NJTSR#678290-00-2-7443-P PCP			
		Proprietary Ingredient	44	N/A	N/A
		NJTSR#678290-00-2-7414-P PCP			
		Proprietary Ingredient	44	N/A	N/A
		NJTSR#678290-00-2-7415-P PCP			
		Proprietary Ingredient	44	N/A	N/A
		NJTSR#678290-00-2-7416-P PCP			
13463-67-7	1-30%	Titanium dioxide	42	10mg/m3	5mg/m3
1333-86-4	1-20%	Carbon black	28	3.5mg/m3	3.5mg/m3
7439-96-5	1-5%	Manganese	20	5mg/m3	0.2mg/m3
7440-50-8	1-5%	Copper	24, 26	0.1mg/m3	0.2mg/m3
7429-90-5	1-30%	Aluminum flake	50, 52, 54, 56	10mg/m3	15mg/m3
141-78-6	1-5%	Ethyl acetate	50, 52, 54, 56	400	400
8052-41-3	1-15%	Stoddard solvent	50, 52, 54, 56	100	100
64742-47-8	1-10%	Aliphatic solvent	50, 52, 54, 56	100	100
12001-26-2	1-5%	Mica		3mg/m3	3mg/m3

#### 4 FIRST AID MEASURES

<b>Inhalation:</b>	If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
<b>Skin Contact:</b>	Promptly flush skin with water until all chemical is removed. Get medical attention if needed.
<b>Eye Contact:</b>	Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Get immediate medical attention.
<b>Ingestion:</b>	Get prompt, qualified medical attention. Seek immediate medical attention. Induce vomiting.

#### 5 FIRE FIGHTING MEASURES

<b>Flash Point:</b>	45 DEGREES F
<b>LEL:</b>	1.2%
<b>UEL:</b>	36.0%
<b>Flammability Classification:</b>	NFPA Class 1B flammable liquid

Dry powder, water spray, dry chemical, carbon dioxide, alcohol foam. Do not use a solid stream of water since the stream will scatter and spread the fire. Water spray may be used to keep fire exposed containers cool, dilute spills to nonflammable mixtures, protect personnel attempting to stop leak and disperse vapors.

#### 6 ACCIDENTAL RELEASE MEASURES

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Absorb spill with inert material, then place in chemical waste container. Remove/Dispose of in a manner consistent with federal and local law. Do not use combustible materials, such as saw dust. Do not flush to sewer. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect attempting to stop leak and to flush spills away from exposures.

#### 7 HANDLING AND STORAGE

# MSDS Material Safety Data Sheet

**Quill Hair & Ferrule LTD**



## Q-COAT DC MIXED COLOR

MSDS Number: P0056

Revision Date: 06/01/10

Page 4 of 7

**Handling Precautions:** Protect against physical damage.

**Storage Requirements:** Store in a cool dry well ventilated area. Keep away from heat and flame. Do not get in eyes, on skin, or on clothing. Protect against physical damage. Outside or detached storage is preferred. Seperate from oxidizing materials. Containers should be bonded and grounded from transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Containers of the material may be hazardous when empty since they retain product residues (vapors,liquid); observe all warnings and precautions listed for the product.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** N/A

**Protective Equipment:** HMIS PP, D | Face Shield and Eye Protection, Gloves, Apron  
Wear appropriate respirator when ventilation is inadequate or when spraying

### 9 PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Colored liquid.	<b>Boiling Point:</b>	148F - 340F
<b>Physical State:</b>	Liquid	<b>Freezing/Melting Pt.:</b>	N/A
<b>Odor:</b>	Organic odor, colored liquid	<b>Solubility:</b>	N/A
<b>pH:</b>	N/A	<b>Spec Grav./Density:</b>	.88
<b>Vapor Pressure:</b>	20 mmHg @ 20 C		
<b>Vapor Density:</b>	Heavier than air		
<b>VOC:</b>	534 GRAMS PER LITER	4.48 LBS PER GALLON	
<b>Evap. Rate:</b>	Slower than ether		
<b>Percent Volatile:</b>	40-80%		

### 10 STABILITY AND REACTIVITY

**Stability:** Product is stable under normal conditions.

**Conditions to avoid:** Oxidation promoting conditions ( Heat, Sunlight and Air), and high temperature

**Materials to avoid (incompatibility):** Strong Oxidizing Agents, alkalies, may attack metallic aluminum at high temperature

**Hazardous Decomposition products:** Carbon dioxide, peroxides, carbon monoxide

**Hazardous Polymerization:** Will not occur.

### 11 TOXICOLOGICAL INFORMATION

# MSDS Material Safety Data Sheet

**Quill Hair & Ferrule LTD**



## Q-COAT DC MIXED COLOR

MSDS Number: P0056

Revision Date: 06/01/10

Page 5 of 7

<b>ACUTE TOXICITY</b>				
<b>Ingredient Name</b>	<b>Test</b>	<b>Results</b>	<b>Route</b>	<b>Species</b>
Titanium dioxide	LD 50	10g/kg	Oral	Rat
	LC 50	N/A	Inhalation	Rat
	LD 50	N/A	Dermal	Rabbit
Carbon black	LD 50	500 mg/kg	Oral	Rat
	LC 50	27000 mg/m3	Inhalation	Rat
	LD 50	1000 mg/kg	Dermal	Rabbit
Manganese	LD 50	>2000 mg/kg	Oral	Rat
	LC 50	N/A	Inhalation	Rat
	LD 50	N/A	Dermal	Rabbit
Cooper	LD 50	152 mg/kg	Oral	Rat
	LC 50	>2.95 mg/L	Inhalation	Rat
	LD 50	>2000 mg/kg	Dermal	Rabbit
Aluminum flake	LD 50	N/A	Oral	Rat
	LC 50	N/A	Inhalation	Rat
	LD 50	N/A	Dermal	Rabbit
Stoddard solvent	LD 50	5000 mg/kg	Oral	Rat
	LC 50	N/A	Inhalation	Rat
	LD 50	3000 mg/kg	Dermal	Rabbit
Ethyl acetate	LD 50	5620 mg/kg	Oral	Rat
	LC 50	200 mg/m3	Inhalation	Rat
	LD 50	>20 ml/kg	Dermal	Rabbit
Aliphatic solvent	LD 50	5mg/kg	Oral	Rat
	LC 50	8200 mg/m3	Inhalation	Rat
	LD 50	500mg/24 H	Dermal	Rabbit
Aliphatic solvent	LD 50	3160 mg/kg	Oral	Rat
	LC 50	2.08 mg/L/ 4 hours	Inhalation	Rat
	LD 50	5000 mg/kg	Dermal	Rabbit

## Q-COAT DC MIXED COLOR

MSDS Number: P0056

Revision Date: 06/01/10

Page 6 of 7

ACUTE TOXICITY				
Ingredient Name	Test	Results	Route	Species
Propylene glycol methyl ether	LD 50	5660 mg/kg	Oral	Rat
	LC 50	1000 ppm / 5 hours	Inhalation	Rat
	LD 50	13000 mg/kg	Dermal	Rabbit
Silica Amorphous	LD 50	3160 mg/kg	Oral	Rat
	LC 50	2.08 mg/L/4 hours	Inhalation	Rat
	LD 50	5000 mg/kg	Dermal	Rabbit
Glycol Ether EB	LD 50	470 mg/kg	Oral	Rat
	LC 50	450 ppm / four hours	Inhalation	Rat
	LD 50	220 mg/kg	Dermal	Rabbit

### 12 ECOLOGICAL INFORMATION

Environmental Fate: When released into the soil, this material is not expected to evaporate significantly. When released into the soil, this material may leach into groundwater. When released into the soil, this material may biodegrade to a moderate extent. When released into water, this material is not expected to evaporate significantly. When released into water, this material may biodegrade to a moderate extent. This material has an estimated bioconcentration factor (BCF) of less than 100. This material is not expected to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals, When released into the air, this material is expected to have the half-life of less than one day.

### 13 DISPOSAL CONSIDERATIONS

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

### 14 TRANSPORT INFORMATION

DOT Class: Flammable Liquid (3) #3

DOT:Paint, 3, UN1263, PG III

IATA:Paint, 3, UN1263, PG III

MULTI-MODAL:Paint, 3, UN1263, PG III

### 15 REGULATORY INFORMATION

\*Titanium dioxide (13463-67-7 1-30%) MASS, OSHAWAC, PA, TSCA, TXAIR

\*Carbon black (1333-86-4 1-20%) MASS, OSHAWAC, PA, TSCA, TXAIR

\*Manganese (7439-96-5 1-5%) MASS, NJHS, OSHAWAC, PA, SARA313, TSCA, TXAIR

\*Copper (7440-50-8 1-5%) CERCLA, EPCRAWPC, MASS, NJHS, OSHAWAC, PA, PRIPOL, SARA313,

# MSDS Material Safety Data Sheet

**Quill Hair & Ferrule LTD**



## Q-COAT DC MIXED COLOR

MSDS Number: P0056

Revision Date: 06/01/10

Page 7 of 7

TOXICPOL, TSCA, TXAIR

\*Aluminum Flake (7429-90-5 1-30%) EPCRAWPC, MASS, NJHS, OSHAWAC, PA, SARA313, TSCA, TXAIR

\*Stoddard solvent (8052-41-3 1-15%) MASS, OSHAWAC, PA, TSCA, TXAIR

\*Ethyl acetate (141-78-6 1-5%) CERCLA, MASS, OSHAWAC, PA, TOXICRCRA, TSCA, TXAIR, TXHWL

\*Aliphatic solvent (64742-47-8 1-10%) TSCA

\*Silica, amorphous (7631-86-9 1-10%) MASS, NJHS, PA, TSCA

\*Glycol Ether EB (111-76-2 10-20%) HAP, MASS, OSHAWAC, PA, TSCA, TXAIR

\*Propylene glycol methyl ether (107-98-2 45-60%) MASS, OSHAWAC, PA, TSCA, TXAIR

### REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List  
OSHAWAC = OSHA Workplace Air Contaminants  
PA = PA Right-To-Know List of Hazardous Substances  
TXAIR = TX Air Contaminants with Health Effects Screening Level  
CERCLA = Superfund clean up substance  
CSWS = Clean Water Act Hazardous substances  
NJHS = NJ Right-to-Know Hazardous Substances  
SARA313 = SARA 313 Title III Toxic Chemicals  
TSCA = Toxic Substances Control Act  
EPCRAWPC = EPCRA Water Priority Chemicals  
PRIPOL = Clean Water Act Priority Pollutants  
TOXICPOL = Clean Water Act Toxic Pollutants  
TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List)  
TXHWL = TX Hazardous Waste List  
HAP = Hazardous Air Pollutants  
PROP65 = CA Prop 65

16

### OTHER INFORMATION

Quill Hair & Ferrule LTD believes that the data contained herein is accurate and derived from qualified sources. The data is not to be taken as a warranty or representation for which Quill Hair & Ferrule LTD assumes legal responsibility. It is offered solely for your consideration, investigation, and verification. Any use of this data and information should be determined by the end user in accordance with Federal, State and local laws and regulations.

END OF MSDS DOCUMENT