

MSDS Material Safety Data Sheet

Quill Hair & Ferrule LTD



Q-COLR CC 3054-Coarse Metallic 54

MSDS Number: C0026

Revision Date: 06/01/10

Page 1 of 4

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Quill Hair & Ferrule LTD
1 Greengate Park Rd.
P.O. Box 23927
Columbia, SC 29224

Contact: Ryan Jones
Telephone Number: 1-803-788-4499
FAX Number: 1-803-736-4731
E-Mail: RyanJ@paint-info.com
Web: www.qhfonline.com

Product Name: Q-COLR CC 3054-Coarse Metallic 54
Revision Date: 06/01/10
MSDS Number: C0026
Common Name: Pigment preparation
Chemical Formula: Complex Mixture
Product Use: Pigment preparation

24 Hours Emergency Number 1-800-451-8346

2 HAZARDS IDENTIFICATION

Route of Entry: Eyes; Ingestion; Inhalation; Skin
Target Organs: Eyes; Skin; Respiratory system; Central nervous system; Hematopoietic system; Blood; Kidneys; Liver; Lymphoid system
Inhalation: Anesthetic, may cause respiratory irritation and CNS depression. Can cause irritation and inflammation of the respiratory tract. Minimal respiratory tract irritation may occur with exposure to a large amount of material.
Skin Contact: May cause irritation, tearing and redness.
Eye Contact: May cause irritation.
Ingestion: Aspiration hazard: Harmful or fatal if swallowed.

HMIS II-ratings (scale 0-4): Health = 1, Fire = 3, Reactivity = 0

HMIS® Rating H1/F3/PH0

NFPA-ratings (scale 0-4): Health = 1, Fire = 3, Reactivity = 0

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Perc.	Chemical Name	ACGIH TLV (PPM)	OSHA PEL (PPM)
7429-90-5	10-20%	Aluminum flake	10mg/m3	15mg/m3
8052-41-3	1-4%	Stoddard solvent	100	100
	1-15%	Polymeric dispersant	N/A	N/A
141-78-6	5-10%	Ethyl acetate	400	400
123-86-4	10-15%	n-Butyl acetate	150	150

MSDS Material Safety Data Sheet

Quill Hair & Ferrule LTD



Q-COLR CC 3054-Coarse Metallic 54

MSDS Number: C0026

Revision Date: 06/01/10

Page 2 of 4

4 FIRST AID MEASURES

Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
Skin Contact: Promptly flush skin with water until all chemical is removed. Get medical attention if needed.
Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Get immediate medical attention.
Ingestion: Seek immediate medical attention. Do not induce vomiting. Do not give anything to drink.

5 FIRE FIGHTING MEASURES

Flash Point: 39 Degrees F
Flash Point Method: Closed Cup
Autoignition Temperature: 964 Degrees F
LEL: 1.2%
UEL: 6.8%
Flammability Classification: NFPA Class 1B flammable liquid

Dry powder, water spray, dry chemical, carbon dioxide, alcohol foam. Do not use a solid stream of water since the stream will scatter and spread the fire. Water spray may be used to keep fire exposed containers cool, dilute spills to nonflammable mixtures, protect personnel attempting to stop leak and disperse vapors. Emits Toxic Fumes under fire conditions.

6 ACCIDENTAL RELEASE MEASURES

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Absorb spill with inert material, then place in chemical waste container. Remove/Dispose of in a manner consistent with federal and local law. Do not use combustible materials, such as saw dust. Do not flush to sewer. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect attempting to stop leak and to flush spills away from exposures.

7 HANDLING AND STORAGE

Handling Precautions: Protect against physical damage.
Storage Requirements: Store in a cool dry well ventilated area. Keep away from heat and flame. Do not get in eyes, on skin, or on clothing. Protect against physical damage. Outside or detached storage is preferred. Separate from oxidizing materials. Containers should be bonded and grounded from transfers to avoid static sparks. Storage and use areas should be No smoking areas. Containers of the material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: N/A
Protective Equipment: HMIS PP, D | Face Shield and Eye Protection, Gloves, Apron
Wear appropriate respirator when ventilation is inadequate or when spraying

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Liquid Paste

MSDS Material Safety Data Sheet

Quill Hair & Ferrule LTD



Q-COLR CC 3054-Coarse Metallic 54

MSDS Number: C0026

Revision Date: 06/01/10

Page 3 of 4

Physical State:	Liquid	Boiling Point:	208.4 Degrees F
Odor:	Mild Camphor-like	Freezing/Melting Pt.:	-79.6 Degrees F
pH:	N/A	Solubility:	N/A
Vapor Pressure:	41.5 mmHg @77 F	Spec Grav./Density:	1.11
Vapor Density:	2.1 g/cm3		

VOC: 485 GR P/LT 4.0 LBS P/GL
Evap. Rate: slower than ether
Percent Volatile: N/A

10 STABILITY AND REACTIVITY

Stability: Product is stable under normal conditions.

Conditions to avoid: Oxidation promoting conditions (Heat, Sunlight and Air).

Materials to avoid (incompatibility): Strong Acids;

Hazardous Decomposition products: Carbon dioxide, oxides of nitrogen, carbon monoxide

Hazardous Polymerization: Will not occur.

11 TOXICOLOGICAL INFORMATION

ACUTE TOXICITY				
Ingredient Name	Test	Results	Route	Species
Ethyl Acetate	LD 50	5620 mg/kg	Oral	Rat
	LC 50	200 mg/m3	Inhalation	Rat
	LD 50	>20 mg/kg	Dermal	Rabbit
Aluminum Flake	LD 50	N/A	Oral	Rat
	LC 50	N/A	Inhalation	Rat
	LD 50	N/A	Dermal	Rabbit
Stoddard Solvent	LD 50	5000 mg/kg	Oral	Rat
	LC 50	N/A	Inhalation	Rat
	LD 50	3000 mg/kg	Dermal	Rabbit
n-Butyl acetate	LD 50	>5000 mg/kg	Oral	Rat
	LC 50	29.2 mg/ L/4 hours	Inhalation	Rat
	LD 50	>5000 mg/kg	Dermal	Rabbit

12 ECOLOGICAL INFORMATION

Environmental Fate: When released into the soil, this material is not expected to evaporate significantly. When released into the soil, this material may leach into groundwater. When released into the soil, this material may biodegrade to a moderate

MSDS Material Safety Data Sheet

Quill Hair & Ferrule LTD



Q-COLR CC 3054-Coarse Metallic 54

MSDS Number: C0026

Revision Date: 06/01/10

Page 4 of 4

extent. When released into water, this material is not expected to evaporate significantly. When released into water, this material may biodegrade to a moderate extent. This material has an estimated bioconcentration factor (BCF) of less than 100. This material is not expected to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals, When released into the air, this material is expected to have the half-life of less than one day.

13 DISPOSAL CONSIDERATIONS

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14 TRANSPORT INFORMATION

DOT Class: Flammable Liquid (3) #3

DOT:Paint, 3, UN1263, PG II

IATA:Paint, 3, UN1263, PG II

MULTI-MODAL:Paint, 3, UN1263, PG II

15 REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Aluminum (7429-90-5 10-20%) EPCRAWPC, MASS, NJHS, OSHAWAC, PA, SARA313, TSCA, TXAIR

*Stoddard solvent (8052-41-3 1-4%) MASS, OSHAWAC, PA, TSCA, TXAIR

*Ethyl acetate (141-78-6 5-10%) CERCLA, MASS, OSHAWAC, PA, TOXICRCRA, TSCA, TXAIR, TXHWL

*n-Butyl acetate (123-86-4 10-15%) CERCLA, CSWHS, MASS, OSHAWAC, PA, TSCA, TXAIR

REGULATORY KEY DESCRIPTIONS

CERCLA = Superfund clean up substance
CSWHS = Clean water Act Hazardous substances
MASS = MA Massachusetts Hazardous Substances List
OSHA = OSHA workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level
NJHS = NJ Right-to-Know Hazardous Substances
SARA313 = SARA 313 Title III Toxic Chemicals
EPCRAWPC = EPCRA Water Priority Chemicals
TSCA = Toxic Substances Control Act
TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List)
TXHWL = TX Hazardous Waste List

16 OTHER INFORMATION

Quill Hair & Ferrule LTD believes that the data contained herein is accurate and derived from qualified sources. The data is not to be taken as a warranty or representation for which Quill Hair & Ferrule LTD assumes legal responsibility. It is offered solely for your consideration, investigation, and verification. Any use of this data and information should be determined by the end user in accordance with Federal, State and local laws and regulations.

END OF MSDS DOCUMENT