

MSDS Material Safety Data Sheet

Quill Hair & Ferrule LTD



Q-BASE PB 0007 PLASTIC MOLDABLE DEFUSED BINDER

MSDS Number: P0073

Revision Date: 10/01/2011

Page 1 of 5

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Quill Hair & Ferrule LTD
1 Greengate Park Rd.
P.O. Box 23927
Columbia, SC 29224

Contact: Deborah Millar
Telephone Number: 1-803-788-4499
FAX Number: 1-803-736-4731
E-Mail: RyanJ@paint-info.com
Web www.qhfonline.com

Product Name: Q-BASE PB 0007 PLASTIC MOLDABLE DEFUSED BINDER
Revision Date: 10/01/2011
MSDS Number: P0073
Common Name: Topcoat
Product Code: QBASEPB0007
Chemical Formula: Complex Mixture
Product Use: Topcoat

24 Hours Emergency Number 1-800-451-8346

2 HAZARDS IDENTIFICATION

Route of Entry: Eyes; Ingestion; Inhalation; Skin
Target Organs: Eyes; Skin; Respiratory system; Central nervous system; Hematopoietic system; Blood; Kidneys; Liver; Lymphoid system
Inhalation: Anesthetic, may cause respiratory irritation and CNS depression. Can cause irritation and inflammation of the respiratory tract. Minimal respiratory tract irritation may occur with exposure to a large amount of material.
Skin Contact: May cause irritation, tearing and redness.
Eye Contact: May cause irritation.
Ingestion: Aspiration hazard: Harmful or fatal if swallowed.

HMIS II-ratings (scale 0-4): Health = 1, Fire = 3, Reactivity = 0

HMIS® Rating H1/F3/PH0

NFPA-ratings (scale 0-4): Health = 1, Fire = 3, Reactivity = 0

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients: Cas #	Perc.	Chemical Name	ACGIH TLV (PPM)	OSHA PEL (PPM)
1330-20-7	1-3%	Xylene	100	100
71-36-3	20-25%	n-Butyl alcohol	20	100
108-88-3	20-15%	Toluene	20	100
64-17-5	30-35%	Ethanol Denatured	1000	1000
112926-00-8	1-5%	Silica, amorphous	10mg/m ³	6mg/m ³
67-56-1	1-3%	Methyl alcohol	200	200
78-93-3	10-15%	Methyl ethyl ketone	200	200

MSDS Material Safety Data Sheet

Quill Hair & Ferrule LTD



Q-BASE PB 0007 PLASTIC MOLDABLE DEFUSED BINDER

MSDS Number: P0073

Revision Date: 10/01/2011

Page 2 of 5

4 FIRST AID MEASURES

Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
Skin Contact: Promptly flush skin with water until all chemical is removed. Get medical attention if needed.
Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Get immediate medical attention.
Ingestion: Get prompt, qualified medical attention. Seek immediate medical attention. Induce vomiting.

5 FIRE FIGHTING MEASURES

Flash Point: 65 DEGREES F
LEL: 1.1%
UEL: 36.0%
Flammability Classification: NFPA Class 1B flammable liquid

Dry powder, water spray, dry chemical, carbon dioxide, alcohol foam. Do not use a solid stream of water since the stream will scatter and spread the fire. Water spray may be used to keep fire exposed containers cool, dilute spills to nonflammable mixtures, protect personnel attempting to stop leak and disperse vapors.

6 ACCIDENTAL RELEASE MEASURES

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Absorb spill with inert material, then place in chemical waste container. Remove/Dispose of in a manner consistent with federal and local law. Do not use combustible materials, such as saw dust. Do not flush to sewer. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect attempting to stop leak and to flush spills away from exposures.

7 HANDLING AND STORAGE

Handling Precautions: Protect against physical damage.
Storage Requirements: Store in a cool dry well ventilated area. Keep away from heat and flame. Do not get in eyes, on skin, or on clothing. Protect against physical damage. Outside or detached storage is preferred. Separate from oxidizing materials. Containers should be bonded and grounded from transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Containers of the material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: N/A
Protective Equipment: HMIS PP, D | Face Shield and Eye Protection, Gloves, Apron
Wear appropriate respirator when ventilation is inadequate or when spraying

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Colorless liquid.
Physical State: Liquid
Boiling Point: 148F - 340F
Odor: Faint ethereal & sweetish
Freezing/Melting Pt.: N/A

MSDS Material Safety Data Sheet

Quill Hair & Ferrule LTD



Q-BASE PB 0007 PLASTIC MOLDABLE DEFUSED BINDER

MSDS Number: P0073

Revision Date: 10/01/2011

Page 3 of 5

pH:	odor.	Solubility:	Miscible 79.4
Vapor Pressure:	N/A	Spec Grav./Density:	.88
Vapor Density:	20 mmHg @ 20 C		
	2.4		
VOC:	722 GRAMS PER LITER	6.02 LBS PER GALLON	
Evap. Rate:	1.75		
Percent Volatile:	86.9%		

10 STABILITY AND REACTIVITY

Stability:	Product is stable under normal conditions.
Conditions to avoid:	Oxidation promoting conditions (Heat, Sunlight and Air), and high temperature
Materials to avoid (incompatibility):	Strong Oxidizing Agents, alkalis, may attack metallic aluminum at high temperature
Hazardous Decomposition products:	Carbon dioxide, peroxides, carbon monoxide
Hazardous Polymerization:	Will not occur.

11 TOXICOLOGICAL INFORMATION

MSDS Material Safety Data Sheet

Quill Hair & Ferrule LTD



Q-BASE PB 0007 PLASTIC MOLDABLE DEFUSED BINDER

MSDS Number: P0073

Revision Date: 10/01/2011

Page 4 of 5

ACUTE TOXICITY				
Ingredient Name	Test	Results	Route	Species
Xylene	LD 50	4300 mg/kg	Oral	Rat
	LC 50	5000 ppm / four hours	Inhalation	Rat
	LD 50	> 1700 mg/kg	Dermal	Rabbit
n-Butyl alcohol	LD 50	2.5 g/kg	Oral	Rat
	LC 50	8000 ppm / four hours	Inhalation	Rat
	LD 50	> 10 ml/kg	Dermal	Rabbit
Methyl Ethyl Ketone	LD 50	4000 mg/kg	Oral	Rat
	LC 50	450 ppm / four hours	Inhalation	Rat
	LD 50	2000 mg/kg	Dermal	Rabbit
Toluene	LD 50	636 mg/kg	Oral	Rat
	LC 50	49000 mg/m ³ / four hours	Inhalation	Rat
	LD 50	12267 mg/kg	Dermal	Rabbit
Ethanol	LD 50	7060 mg/kg	Oral	Rat
	LC 50	64000 ppm / four hours	Inhalation	Rat
	LD 50	15800 mg/kg	Dermal	Rabbit
Methyl Alcohol	LD 50	5600 mg/kg	Oral	Rat
	LC 50	64000 ppm / four hours	Inhalation	Rat
	LD 50	15800 mg/kg	Dermal	Rabbit
Silica,amorphous	LD 50	3160 mg/kg	Oral	Rat
	LC 50	2.08 mg/L four hours	Inhalation	Rat
	LD 50	5000 mg/kg	Dermal	Rabbit

12

ECOLOGICAL INFORMATION

Environmental Fate: When released into the soil, this material is not expected to evaporate significantly. When released into the soil, this material may leach into groundwater. When released into the soil, this material may biodegrade to a moderate extent. When released into water, this material is not expected to evaporate significantly. When released into water, this material may biodegrade to a moderate extent. This material has an estimated bioconcentration factor (BCF) of less than 100. This material is not expected to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals, When released into the air, this material is expected to have the half-life of less than one day.

13

DISPOSAL CONSIDERATIONS

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14

TRANSPORT INFORMATION

DOT Class: Flammable Liquid (3) #3

MSDS Material Safety Data Sheet

Quill Hair & Ferrule LTD



Q-BASE PB 0007 PLASTIC MOLDABLE DEFUSED BINDER

MSDS Number: P0073

Revision Date: 10/01/2011

Page 5 of 5

DOT:Paint, 3, UN1263, PG II

IATA:Paint, 3, UN1263, PG II

MULTI-MODAL:Paint, 3, UN1263, PG II

15 REGULATORY INFORMATION

*Xylene (1330-20-7 1-3%) CERCLA, CSWHS, EPCRAWPC, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TXAIR, TXHWL

*n-Butyl alcohol (71-36-3 20-25%) CERCLA, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TXAIR, TXHWL

*Toluene (108-88-3 10-15%) CERCLA, CSWHS, EPCRAWPC, HAP, MASS, NJHS, OSHAWAC, PA, PRIPOL, PROP65, SARA313, TOXICPOL, TOXICRCRA, TXAIR, TXHWL

*Ethanol Denatured (64-17-5 30-35%) MASS, OSHAWAC, PA, TXAIR

*Silica, amorphous (112926-00-8 1-5%) MASS, OSHAWAC, TXAIR

*Methyl alcohol (67-56-1 1-3%) CERCLA, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

*Methyl ethyl ketone (78-93-3 10-15%) CERCLA, HAP, HWRCRA, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

REGULATORY KEY DESCRIPTIONS

- HAP = Hazardous Air Pollutants
- MASS = MA Massachusetts Hazardous Substances List
- OSHA = OSHA workplace Air Contaminants
- PA = PA Right-To-Know List of Hazardous Substances
- TXAIR = TX Air Contaminants with Health Effects Screening Level
- CERCLA = Superfund clean up substance
- CSWHS = Clean water Act Hazardous substances
- EPCRAWPC = EPCRA water Priority Chemicals
- NJEHS = NJ Extraordinarily Hazardous Substances
- NJHS = NJ Right-to-Know Hazardous Substances
- NRC = Nationally Recognized Carcinogens
- OSHAHTS = OSHA Hazardous and Toxic Substances
- OSHA PSM = OSHA Chemicals Requiring process safety management
- PROP65 = CA Prop 65
- SARA313 = SARA 313 Title III Toxic Chemicals
- TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List)
- TXHWL = TX Hazardous Waste List
- HWRCRA = RCRA Hazardous Wastes
- PRIPOL = Clean Water Act Priority Pollutants
- TOXICPOL = Clean Water Act Toxic Pollutants
- TSCA = Toxic Substances Control Act

16 OTHER INFORMATION

Quill Hair & Ferrule LTD believes that the data contained herein is accurate and derived from qualified sources. The data is not to be taken as a warranty or representation for which Quill Hair & Ferrule LTD assumes legal responsibility. It is offered solely for your consideration, investigation, and verification. Any use of this data and information should be determined by the end user in accordance with Federal, State and local laws and regulations.

END OF MSDS DOCUMENT