



## Safety Data Sheet

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	29-7566-2	<b>Version Number:</b>	7.00
<b>Issue Date:</b>	07/17/14	<b>Supersedes Date:</b>	08/07/13

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Perfect-It™ EX Rubbing Compound, 36058, 36059, 36060, 36061, 36062, 36063, 36064

#### Product Identification Numbers

LB-K100-0995-1, LB-K100-1027-1, LB-K100-1184-6, LB-K100-1311-6, LB-K100-1347-8, 60-4550-7010-6, 60-4550-7028-8, 60-4550-7048-6, 60-4550-7049-4, 60-4550-7050-2, 60-4550-7119-5

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive, Rubbing Compound

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Automotive Aftermarket
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Skin Sensitizer: Category 1.

#### 2.2. Label elements

##### Signal word

Warning

##### Symbols

Exclamation mark |

##### Pictograms

**Hazard Statements**

May cause an allergic skin reaction.

**Precautionary Statements****General:**

Keep out of reach of children.

**Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Hazards not otherwise classified**

None.

## SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	40 - 70 Trade Secret *
Aluminum Oxide	1344-28-1	10 - 30 Trade Secret *
Hydrotreated Light Petroleum Distillates	64742-47-8	10 - 30 Trade Secret *
White Mineral Oil (Petroleum)	8042-47-5	1 - 5 Trade Secret *
Glycerin	56-81-5	1 - 5 Trade Secret *
Ethylene Oxide, Polymer with Ethylenediamine and Propylene Oxide	26316-40-5	<= 0.9 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures**

**5.1. Suitable extinguishing media**

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

**7.2. Conditions for safe storage including any incompatibilities**

Keep from freezing.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Aluminum Oxide	1344-28-1	CMRG	TWA:1 fiber/cc	
Aluminum Oxide	1344-28-1	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Glycerin	56-81-5	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Hydrotreated Light Petroleum Distillates	64742-47-8	CMRG	TWA:165 ppm	
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	Skin Notation, A3: Confirmed animal carcin.
MINERAL OILS, HIGHLY-REFINED OILS	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
Paraffin oil	8042-47-5	OSHA	TWA(as mist):5 mg/m3	
White Mineral Oil (Petroleum)	8042-47-5	CMRG	TWA:5 mg/m3;STEL:10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists  
 AIHA : American Industrial Hygiene Association  
 CMRG : Chemical Manufacturer's Recommended Guidelines  
 OSHA : United States Department of Labor - Occupational Safety and Health Administration  
 TWA: Time-Weighted-Average  
 STEL: Short Term Exposure Limit  
 CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**

Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>General Physical Form:</b>	Liquid
<b>Odor, Color, Grade:</b>	Tan liquid slight pine oil odor
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	7.5 - 9
<b>Melting point</b>	<i>No Data Available</i>
<b>Boiling Point</b>	<i>No Data Available</i>
<b>Flash Point</b>	>=200 °F [ <i>Test Method:</i> Closed Cup]
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<i>No Data Available</i>
<b>Vapor Density</b>	<i>No Data Available</i>
<b>Density</b>	1.05 - 1.1 g/ml
<b>Specific Gravity</b>	1.05 - 1.1 [ <i>Ref Std:</i> WATER=1]
<b>Solubility In Water</b>	<i>No Data Available</i>
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity</b>	30,000 - 35,000 centipoise
<b>Hazardous Air Pollutants</b>	0.008 lb HAPS/lb solids [ <i>Test Method:</i> Calculated]
<b>Volatile Organic Compounds</b>	174 g/l [ <i>Test Method:</i> calculated SCAQMD rule 443.1]
<b>Volatile Organic Compounds</b>	16.2 % weight [ <i>Test Method:</i> calculated per CARB title 2]
<b>Percent volatile</b>	78.3 % weight
<b>VOC Less H2O &amp; Exempt Solvents</b>	524 g/l [ <i>Test Method:</i> calculated SCAQMD rule 443.1]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Hydrotreated Light Petroleum Distillates	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrotreated Light Petroleum Distillates	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3.0 mg/l
Hydrotreated Light Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminum Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg
White Mineral Oil (Petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White Mineral Oil (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
Aluminum Oxide	Rabbit	No significant irritation
Glycerin	Rabbit	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
Aluminum Oxide	Rabbit	No significant irritation
Glycerin	Rabbit	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	Mild irritant

**Skin Sensitization**

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Guinea pig	Not sensitizing
Glycerin	Guinea pig	Not sensitizing
White Mineral Oil (Petroleum)	Guinea pig	Not sensitizing

**Respiratory Sensitization**

Name	Species	Value
------	---------	-------

**Germ Cell Mutagenicity**

Name	Route	Value
Hydrotreated Light Petroleum Distillates	In Vitro	Not mutagenic
Aluminum Oxide	In Vitro	Not mutagenic
White Mineral Oil (Petroleum)	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Hydrotreated Light Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Aluminum Oxide	Inhalation	Rat	Not carcinogenic
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
White Mineral Oil (Petroleum)	Dermal	Mouse	Not carcinogenic
White Mineral Oil (Petroleum)	Inhalation	Multiple animal	Not carcinogenic

		species	
--	--	---------	--

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Glycerin	Ingestion	Not toxic to female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not toxic to male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not toxic to development	Rat	NOAEL 2,000 mg/kg/day	2 generation
White Mineral Oil (Petroleum)	Ingestion	Not toxic to female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not toxic to male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not toxic to development	Rat	NOAEL 4,350 mg/kg/day	during gestation

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Hydrotreated Light Petroleum Distillates	Inhalation	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Hydrotreated Light Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Aluminum Oxide	Inhalation	pneumoconiosis   pulmonary fibrosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Glycerin	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Inhalation	heart   liver   kidney and/or bladder	All data are negative	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system   hematopoietic system   liver   kidney and/or bladder	All data are negative	Rat	NOAEL 10,000 mg/kg/day	2 years
White Mineral Oil (Petroleum)	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,381 mg/kg/day	90 days
White Mineral Oil (Petroleum)	Ingestion	liver   immune system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,336 mg/kg/day	90 days

**Aspiration Hazard**

Name	Value
Hydrotreated Light Petroleum Distillates	Aspiration hazard
White Mineral Oil (Petroleum)	Aspiration hazard



Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No    Pressure Hazard - No    Reactivity Hazard - No    Immediate Hazard - Yes    Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Aluminum Oxide	1344-28-1	10 - 30
Aluminum Oxide (ALUMINUM OXIDE (FIBROUS FORMS ONLY))	1344-28-1	10 - 30

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

#### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### SECTION 16: Other information

#### NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	29-7566-2	<b>Version Number:</b>	7.00
<b>Issue Date:</b>	07/17/14	<b>Supersedes Date:</b>	08/07/13

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at [www.3M.com](http://www.3M.com)