

MATERIAL SAFETY DATA SHEET

PolyGard, Inc. - PGAR
Prod # 7200001

FINISH KARE PRODUCTS, INC.
SOUTH EL MONTE, CALIFORNIA
(626) 443-8983

HAZARD RATINGS

MINIMAL.....0	HEALTH	1
SLIGHT.....1	-----	-----
MODERATE.....2	FLAMMABILITY	1
SERIOUS.....3	-----	-----
SEVERE.....4	REACTIVITY	0
	-----	-----

SECTION I PRODUCT IDENTIFICATION

TRADE NAME:	PART NO:	V.O.C. GRM/LT
PREMIUM MOLD RELEASE WAX.....	1165	356.06
ANTI STATIC PASTE WAX.....	1100P	356.06
HI LOW PASTE WAX.....	1000P	356.06
HI TEMP STABILITY.....	1000HTS	356.06
MOLD RELEASE PASTE WAX.....	1006	356.06
BRUSH GEL RELEASE WAX.....	1004-23	356.06
EASY ON EASY OFF.....	88M	356.06
EDGE WAX.....	68	356.06
MOLD SEALER & RELEASE AGENT.....	604-B	356.06
BLUE MOLD RELEASE WAX.....	333MR	356.06
MOLD SAVER.....	2000	356.06
HI TEMP RELEASE WAX.....	104	356.06

CHEMICAL NAME: HYDROCARBON MIXTURE

SECTION II HAZARDOUS INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS
CAS NO. % PEL/OSHA TLV/ACGIH VOC

ALIPHATIC HYDROCARBON	64742-96-7	50-60%
ALIPHATIC HYDROCARBON MIXTURE	8052-41-3	15-20%
WAX BLEND: HYDROCARBON WAX MIXTURE		
SYNTHETIC HYDROCARBON	}	15-20%

SECTION III HEALTH HAZARD INFORMATION

THE HEALTH EFFECT NOTED BELOW ARE CONSISTENT WITH REQUIREMENTS UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29CFR 1910.1200)

EYE CONTACT: Product is minimally irritating to the eyes.

SKIN CONTACT: Prolonged or repeated contact may result in defatting and drying of the skin.

INHALATION (BREATHING): N/A. Paste product.

INGESTION (SWALLOWING): Ingestion of product may result in vomiting; aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonitis.

EYE CONTACT: Flush the eye(s) with plenty of water for 15 minutes while holding eyelids open.

SKIN CONTACT: Wash with soap and water.

ORIG

=====

SECTION IV EMERGENCY FIRST AID AND PROCEDURES

=====

INHALATION (BREATHING): N/A. Paste Product

INGESTION (SWALLOWING): Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

=====

SECTION IV PHYSICAL DATA

=====

BOILING POINT: (DEG F) 318-388	SPECIFIC GRAVITY: (H2O=1) 0.797	VAPOR PRESSURE: (MM HG) 5.3 @ 100 F
-----------------------------------	------------------------------------	--

MELTING POINT: (DEG F) 250 degrees	SOLUBILITY IN WATER: Neg.	VAPOR DENSITY: (AIR=1) 4.1
---------------------------------------	------------------------------	-------------------------------

EVAPORATION RATE (N-BUTYL ACETATE=1) .13 * ESTIMATED

APPEARANCE AND ODOR: hydrocarbon odor -

=====

SECTION VI FIRE AND EXPLOSION HAZARDS

=====

FLASH POINT AND METHOD: EST. N/A F TCC	FLAMMABLE LIMITS /% VOLUME IN AIR LOWER 1 UPPER: 7
---	---

FIRE AND EXPLOSION HAZARDS: Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture.

FIRE FIGHTING PROCEDURES: Do not enter confined fire space without full bunker gear, including a positive NIOSH approved self-contained apparatus. Cool fire exposed containers with water.

EXTINGUISHING MEDIA: Use water fog, dry chemical or CO2. Do not use a direct stream of water.

=====

SECTION VII REACTIVITY

=====

STABILITY: Stable HAZARDOUS DEPOLIMERIZATION: will not occur

INCOMPATIBILITY (MATERIAL TO AVOID): Avoid heat, sparks, flame and contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS:

=====

SECTION VIII EMPLOYEE PROTECTION

=====

VENTILATION: Not required. /

RESPIRATORY PROTECTION: Normally not required.

PROTECTIVE GLOVES: Normally not required.

EYE PROTECTION: Normally not required.

=====

OTHER PROTECTIVE EQUIPMENT: Normally not required.

=====

SECTION IX

ENVIRONMENTAL PROTECTION

=====

PRECAUTION IN CASE OF RELEASE OR SPILL: Eliminate potential sources of ignition. Dike and contain. Soak up residue with an absorbent material such as clay sand or other suitable material.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal regulations.

HANDLING AND STORAGE PRECAUTIONS: Handle as combustible liquid. Always wash hands thoroughly after handling these products.

SECTION X

TRANSPORTATION REQUIREMENTS

=====

DEPARTMENT OF TRANSPORTATION CLASSIFICATION:

D.O.T. PROPER SHIPPING NAME: N/A

OTHER REQUIREMENTS:

24 HOUR EMERGENCY ASSISTANCE " CHEM-TEL 1-800-255-3924 "

SARA SECTION 313 NOTIFICATION

I. Chemicals subject to the reporting requirements of Sara Tittle III, Section 313 are identified in Section II Hazardous Ingredients. Proposition 65 warning: (#) This mark following a chemical listed in Section II designates material known to the state of California to cause cancer, birth defects, or other reproductive harm. Other ingredients may in addition contain trace amounts of these known carcinogens or teratogens.

II. E.P.A. Sara Title III Section 313 listed toxic chemical is present as follows:

Not applicable

III. The information contained herein is based on the data available to us and is believed to be correct. However, Finish Kare Products assumes no responsibility for injury from the use of the product described herein.

Date prepared: January 1, 2003 By: FLM

FINISH KARE PRODUCTS, INC.
1726 FLORADALE AVE.
SO. EL MONTE, CA 91733

BE SAFE...READ OUR PRODUCT SAFETY INFORMATION...AND PASS IT ON!