

MATERIAL SAFETY DATA SHEET

FINISH KARE PRODUCTS, INC.
SOUTH EL MONTE, CALIFORNIA

sales@finishkare.com

(626) 443-8983

HAZARD RATINGS

MINIMAL.....0	HEALTH	2
SLIGHT.....1	-----	-----
MODERATE.....2	FLAMMABILITY	1
SERIOUS.....3	-----	-----
SEVERE.....4	REACTIVITY	0
	-----	-----

SECTION I PRODUCT IDENTIFICATION

TRADE NAME: BLUE WAX.....333MR PART NO: V.O.C. GRM/LT 356.06

CHEMICAL NAME: HYDROCARBON MIXTURE

SECTION II HAZARDOUS INGREDIENTS

OCCUPATIONAL EXPOSURE

LIMITS

	CAS NO.	%	PEL/OSHA	TLV/ACGIH	VOC
LOW ODOR BASE SOLVENT	64742-47-8	35-55	5.0 MG/M3	200ppm	
AROMATIC HYDROCARBON*	64742-95-6	15-25	*	*	
ALIPHATIC HYDROCARBON	8052-41-3	07-15	500PPM	100PPM	
WAX BLEND	8015-86-9	25-30			
* COMPONENTS-	CAS #	Max %			
1,2,4, TRIMETHYL BENZENE	95-63-6	32.0	25	25	
Xylene	1330-20-7	2.2	100	100	
Cumene	98-82-8	1.5	50	50	

SECTION III HEALTH HAZARD INFORMATION

THE HEALTH EFFECT NOTED BELOW ARE CONSISTENT WITH REQUIREMENTS UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29CFR 1910.1200)

EYE CONTACT: Product is minimally irritating to the eyes.

SKIN CONTACT: Prolonged or repeated contact may result in defatting and drying of the skin.

INHALATION(BREATHING): N/A. Paste product.

INGESTION(SWALLOWING): Ingestion of product may result in vomiting; aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonitis.

EYE CONTACT: Flush the eye(s) with plenty of water for 15 minutes while holding eyelids open.

SKIN CONTACT: Wash with soap and water.

SECTION IV EMERGENCY FIRST AID AND PROCEDURES

INHALATION(BREATHING): N/A. Paste Product
INGESTION(SWALLOWING): Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

SECTION V PHYSICAL DATA

BOILING POINT: 318-388 °F
SPECIFIC GRAVITY: (H2O=1) 0.797
VAPOR PRESSURE: (MM HG) 5.3 @ 100 F

MELTING POINT: 250 °F
SOLUBILITY IN WATER: Negligible
VAPOR DENSITY: (AIR=1) 4.1

EVAPORATION RATE (N-BUTYL ACETATE=1) .13 ESTIMATED

% VOLATILE BY WEIGHT: APPROXIMATELY 65-70%

APPEARANCE AND ODOR: 333MR- BLUE (HYDROCARBON ODOR)

SECTION VI FIRE AND EXPLOSION HAZARDS

FLASH POINT AND METHOD: 106°F PENSKEY-MASTER CLOSED CUP

FLAMMABLE LIMITS/% VOLUME IN AIR: LOWER 1 - UPPER 7

FIRE AND EXPLOSION HAZARDS: Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture.

FIRE FIGHTING PROCEDURES: Do not enter confined fire space without full bunker gear, including a positive NIOSH approved self-contained apparatus. Cool fire exposed containers with water.

EXTINGUISHING MEDIA: Use water, fog, dry chemical or CO2. Do not use a direct stream of water.

SECTION VII REACTIVITY

STABILITY: Stable
HAZARDOUS DEPOLIMERIZATION: will not occur.

INCOMPATIBILITY (MATERIAL TO AVOID): Avoid heat, sparks, flame and contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS:

SECTION VIII EMPLOYEE PROTECTION

VENTILATION: Not required.

RESPIRATORY PROTECTION: Normally not required.

PROTECTIVE GLOVES: Normally not required.

EYE PROTECTION: Normally not required.

OTHER PROTECTIVE EQUIPMENT: Normally not required.

MATERIAL SAFETY DATA SHEET (333MR)

PAGE 3

=====
=
SECTION IX ENVIRONMENTAL PROTECTION
=====

PRECAUTION IN CASE OF RELEASE OR SPILL: Eliminate potential sources of ignition. Dike and contain. Soak up residue with an absorbent material such as clay sand or other suitable material.

WASTE DISPOSAL METHOD: Dispose of in accordance with **local, state and federal** regulations.

HANDLING AND STORAGE PRECAUTIONS: Handle as combustible liquid. Always wash hands thoroughly after handling these products.(Protect from freezing, do not storage on temperature above 85°F)

=====
=
=SECTION X TRANSPORTATION REQUIREMENTS
=====

U.S. DEPARTMENT OF TRANSPORTATION(DOT)CLASSIFICATION: **FLAMMABLE SOLIDS, Not DOT regulated on trucks in containers of < 1 KG or 2.2 LBS.**

IATA/IMO/IMDG : Not regulated under limited quantity of < 1 kg or 2.2 Pounds

DESCRIPTION : FLAMMABLE SOLID, ORGANIC, N.O.S.(PETROLEUM DISTILLATES) Class 4.1, UN 1325, PG II

OTHER REQUIREMENTS:

Emergency Telephone number: 800-535-5053 and 352-323-3500

SARA SECTION 313 NOTIFICATION

I. Chemicals subject to the reporting requirements of Sara Title III, Section 313 are identified in Section II Hazardous Ingredients. Proposition 65 warning: (#) This mark following a chemical listed in Section II designates material known to the state of California to cause cancer, birth defects, or other reproductive harm. Other ingredients may in addition contain trace amounts of these known carcinogens or teratogens.

II. E.P.A. Sara Title III Section 313 listed toxic chemical is present as follows: Not applicable

III. The information contained herein is based on the data available to us and is believed to be correct. However, Finish Kare Products assumes no responsibility for injury from the use of the product described herein.

Date prepared: March 01, 2011 By: J. JHAVERI

BE SAFE...READ OUR PRODUCT SAFETY INFORMATION...AND PASS IT ON!