

MATERIAL SAFETY DATA SHEET
 FINISH KARE PRODUCTS, INC.
 SOUTH EL MONTE, CALIFORNIA
Sales@finishkare.com
 (626) 443-8983

HAZARD RATINGS

MINIMAL.....0	HEALTH	2
SLIGHT.....1	-----	-----
MODERATE.....2	FLAMMABILITY	2
SERIOUS.....3	-----	-----
SEVERE.....4	REACTIVITY	0
	-----	-----

=====

=SECTION I PRODUCT IDENTIFICATION

=====

=

TRADE NAME:	PART NO:	V.O.C.
HI LOW LIQUID WAX.....1000L		6.141b/gl
ANTI STATIC HI LOW LIQUID WAX.....1000L A.S.		6.141b/gl
ANTI STATIC LIQUID RELEASE WAX SPRAYABLE.....1000L-28 A.S.		6.141b/gl

CHEMICAL NAME: Aromatic Hydrocarbon

=====

=SECTION II HAZARDOUS INGREDIENTS

=====

OCCUPATIONAL EXPOSURE

LIMITS

	CAS NO.	%	PEL/OSHA	TLV/ACGIH	VOC
Aromatic Solvent	64742-95-6	65-75	400ppm	400	
Aliphatic Petroleum	8052-41-3	15-20			
Wax Blend:		5-10			

=====

=SECTION III HEALTH HAZARD INFORMATION

=====

THE HEALTH EFFECT NOTED BELOW ARE CONSISTENT WITH REQUIREMENTS UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29CFR 1910.1200)

EYE CONTACT: May be irritating to the eyes.
 High vapor concentrations may also be irritating.

SKIN CONTACT: Liquid may be irritating to the skin. Prolonged or repeated contact may result in de-fatting and drying of the skin.

INHALATION(BREATHING): Vapors may be irritating to the nose, throat and respiratory tract.
 High vapor concentrations may cause CNS depression.

INGESTION(SWALLOWING): Ingestion of product may result in vomiting; aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonitis.

MATERIAL SAFETY DATA SHEET(1000L,1000L A.S.& 1000L-28) PAGE 2

=====

=SECTION IV EMERGENCY FIRST AID AND PROCEDURES

=====

=

EYE CONTACT: Flush the eye(s) with plenty of water for 15 minutes while holding eyelids open

SKIN CONTACT: Remove contaminated clothing and wipe excess from skin. Rinse off residue, then wash with soap and water. If irritation occurs, get medical attention.

INHALATION(BREATHING): Remove victim to air free of vapors and provide oxygen if breathing is difficult. Give artificial respiration if not breathing and get immediate medical attention.

INGESTION(SWALLOWING): Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

=====

=SECTION V PHYSICAL DATA

=====

=

BOILING POINT: 313-395 °F	SPECIFIC GRAVITY: (H2O=1) 0.86	VAPOR PRESSURE: (MM HG) 3.00 Estimated
------------------------------	-----------------------------------	---

MELTING POINT: Not Established	SOLUBILITY IN WATER: Negligible	VAPOR DENSITY: (AIR=1) 4.4
-----------------------------------	------------------------------------	-------------------------------

EVAPORATION RATE (N-BUTYL ACETATE=1) 0.6 ESTIMATED

APPEARANCE AND ODOR: hydrocarbon odor

=====

=

SECTION VI FIRE AND EXPLOSION HAZARDS

=====

FLASH POINT AND METHOD: EST. 112 °F TCC

FLAMMABLE LIMITS /% VOLUME IN AIR: LOWER 0.9 UPPER: 6.0 Approx.

FIRE AND EXPLOSION HAZARDS: Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture.

FIRE FIGHTING PROCEDURES: Do not enter confined fire space without full bunker gear, including a positive NIOSH approved self-contained apparatus. Cool fire exposed containers with water.

EXTINGUISHING MEDIA: Use water fog, dry chemical or CO2. Do not use a direct stream of water.

=====

=SECTION VII REACTIVITY

=====

STABILITY: Stable HAZARDOUS DEPOLIMERIZATION: Will not occur
INCOMPATIBILITY (MATERIAL TO AVOID): Avoid heat, sparks, flame and contact with strong oxidizing agents.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

=====
SECTION VIII EMPLOYEE PROTECTION
=====

=
VENTILATION: If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional ventilation or exhaust system may be required.

RESPIRATORY PROTECTION: The use of respirator protection is advised when concentrations exceed the established exposure limits. Depending on the airborne concentrations, use a respirator or gas mask with appropriate cartridges and canisters

PROTECTIVE GLOVES: The use of impermeable gloves is advised to prevent skin contact.

EYE PROTECTION: Goggles, eye guard to prevent eye contact or injury.

OTHER PROTECTIVE EQUIPMENT: It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

MATERIAL SAFETY DATA SHEET (1000L & 1000L-AS) PAGE 3

=====
SECTION IX ENVIRONMENTAL PROTECTION
=====

=
PRECAUTION IN CASE OF RELEASE OR SPILL: Combustible. Keep away from all sources of ignition. Evacuate area of unprotected personnel. Wear appropriate respirator and protective clothing. Dike and contain. Remove with vacuum truck or pump to storage vessel. Soak up residue with absorbent like sand or clay.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal regulations.

HANDLING AND STORAGE PRECAUTIONS: Handle as combustible liquid. Keep containers tightly closed, cool, dry and away from all sources of ignition. Use and store with adequate ventilation. Avoid inhalation of vapors and personal contact with products. Always wash hands thoroughly after handling these products. Empty containers contain residue, do not expose to heat, flame or sparks.

=====
SECTION X TRANSPORTATION REQUIREMENTS
=====

=
DEPARTMENT OF TRANSPORTATION CLASSIFICATION:

DOT SHIPPING NAME: Bulk – Petroleum Distillates, N.O.S., Combustible Liquid, UN 1268, PG III
Combustible Liquid, NOT REGULATED on trucks in containers of < 119 Gallons, DRUM LABEL: NONE
IATA/ICAO: Petroleum Distillates, N.O.S.(UN 1268)
IMO/IMDG: Petroleum Distillates, N.O.S.(UN 1268)
OTHER REQUIREMENTS: Quantity Limitations: Passenger aircraft/rail 60L or about 15.85 gals; Cargo aircraft only 220 L or 58 gals.

Emergency Telephone number: 800-535-5053 and 352-323-3500

All ingredients are listed under USA TSCA, Canada Domestic Substance List (DSL) & European

SARA SECTION 313 NOTIFICATION

I. Chemicals subject to the reporting requirements of Sara Title III, Section 313 are identified in Section II Hazardous Ingredients. Proposition 65 Warning :(#) This mark following a chemical listed in Section II designates material known to the state of California to cause cancer, birth defects, or other reproductive harm. Other ingredients may in addition contain trace amounts of these known carcinogens or teratogens.

II. E.P.A. Sara Title III Section 313 listed toxic chemical is present as follows:
Not applicable

III. The information contained herein is based on the data available to us and is believed to be correct. However, it is not warranted. Finish Kare Products cannot control the use and its conditions by the users, thus it is a responsibility of the recipient and the user to determine the suitability of its use. And FK assumes no responsibility for injury from the use of the product described herein.

MSDS REVISION Date: March 01, 2011

By: J. Jhaveri

BE SAFE...READ OUR PRODUCT SAFETY INFORMATION...AND PASS IT ON!